

LINE RITE

DESCRIPTION:

Clear-coat acrylic coating for use in sealing tape prior to the subsequent application of lines for recreational or light traffic areas.

SURFACE USES:

Asphalt and color-coated or concrete surfaces. For use on athletic courts or other areas to be marked with line paint.

APPLICATION:

Brush, roller or airless spray & marking equipment.

DRYING TIME:

• 30 minutes to one hour – 1 coat

COLOR RANGE:

Clear

COVERAGE:

Approximately 150-200 square feet per gallon. (One gallon generally required a court 481 linear feet – 2" wide lines).

LIMITATIONS:

- Apply only when ambient temperature is 50°F and rising or less than 140°F
- Do not apply when rain or high humidity is imminent.
- Keep from freezing. Do not store in hot sun.
- Keep containers tightly closed when not in use.
- Allow asphalt to cure at least 14 days.

APPLICATION SPECIFICATIONS

Line Rite should be applied over tape, prior to the painting of lines. Lay out masking tape, painters' tape or similar, along either side of the line to be painted. Apply Line Rite product, using a brush, roller or sprayer so that it covers the inside edge of the tape on both sides. On bare asphalt or other rougher surfaces, a second coat of Line Rite may be necessary to ensure that the tape is completely sealed down.

After 30 minutes, Line Paint, either colored or white, should be applied by roller, brush or sprayer over the same area. Some Line Rite will bleed under the tape, but it will dry clear. The Line Rite should seal the tape edge, preventing subsequent Line Paint from bleeding under the tape, resulting in a crisp, clean line.

LIMITATIONS:

Apply only when ambient surface and air temperature are a minimum 50°F (10°C) and rising.

Do not apply when rain or high humidity is imminent.

The surface should be sound, free of cracks and deterioration.

The surface should be clean of all contaminants.

Keep from freezing.

Do not store in the direct sunlight.

Once opened, entire contents should be used.

Shaded and Indoor areas will dry more slowly.

