

CSS MULTI PATCH

Description

CSS Multi Patch is a ready to use, acrylic patching compound suitable for filling cracks and other non structural defects in asphalt, concrete surfaces prior to application of **Synpave, Rebound Ace Pro, Rebound Ace HSA, Rebound Ace GS8, Rebound Ace Impact, Rebound Ace Air Cushion.**

Product Features

High Build (up to 12mm filling in a single application)
Compatible with all Rebound Ace Sports Surfaces
Suitable for patching between acrylic coats (especially relevant to filling of "bird baths") in hardcourts.

Preparation and Application

Prepare the surface ready for application of **Rebound Ace Sports Surfaces** in accordance with the Technical Bulletin for the particular type of substrate.

In most applications, apply the product without thinning using a trowel, steel float, putty knife or metal straight edge. When filling deep holes or cracks, more than one application may be necessary to obtain a smooth finish, and to speed the cure through of the product.

Allow the first application to dry for a minimum six (6) hours before applying further coats. Full cure through is essential before repeating the application of **CSS Multi Patch** or applying other coatings over the patched area. **CSS Multi Patch** can appear hard and cured on top and still be uncured below particularly if applied on non-absorbent base. Check for full cure of lower layer.

When filling broad areas such as "bird baths", thinning the final application of product up to 5 % maximum by volume with potable water, will assist in spreading the product smoothly to a fine feathered edge. A straight edge or screed bar is the suggested tool for this type of work.

CSS Multi Patch can be sanded and ground smooth post application before surfacing

Clean Up

Clean up tools and equipment immediately after use with clean water.

Restrictions

Do not use **CSS Multi Patch**

- when surface temperature is less than, or expected to be less than 10 °C in the next 4 hrs after application
- for filling of expansion joints or cracks in concrete or asphalt slabs where movement is designed or likely to occur. An elastomeric filler is required for this purpose
- over or on the topside of Rebound Ace Sports cushion surface systems.

If structural movement of the slab continues it is likely that hairline cracking will occur.

Packaging

CSS Multi Patch is supplied in 10 Litre resealable plastic containers.

Important: The information, and the recommendations relating to the application/s and end use of California Sports Surfaces Products, are given in good faith based on California Sports Surfaces current knowledge and experience of the products when properly stored, handled, and applied in normal conditions. In practice, the differences in substrates, materials and actual site conditions are such that no warranty in respect of the merchantability or of suitability for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. Users should always refer to the most recent issue of the Australian version of the Technical Bulletin for the product concerned, copies of which are supplied on request. PLEASE CONSULT TECHNICAL DEPARTMENT FOR PRODUCT RECOMMENDATIONS AND ADVICE. PRE-TESTING OF SUBSTRATES IS RECOMMENDED TO ENSURE PERFORMANCE OF PRODUCT UNDER ALL CONDITIONS.