



## HI-HIDE PLEXICOLOR® LINE PAINT

### DESCRIPTION:

Highly pigmented marking paint for use over any bituminous surface or color coating system in recreational or light traffic areas. The finished application is non-glaring, highly resistant to climatic conditions, fast drying easily applied, and provides excellent hiding. Plexicolor Line Paint will not cause crazing, cracking, peeling, or deterioration to asphalt that is typical of solvent-type traffic paints. Also available as a textured-line paint.

### SURFACE USES:

Asphalt and color-coated or concrete surfaces:

- Tennis Courts
- Play Areas
- Curbs and Berms
- Running Tracks
- Parking Lots
- Restricted Travel Roadways  
(Not subjected to wet abrasion)

### APPLICATION:

- Brush
- Roller
- Spray and Marking Equipment
- Airless Spray

### DRYING TIME:

- 30 minutes to one hour – 1 coat

### COLOR RANGE:

White, Yellow, Red, Blue, Green, Orange, Black

### COVERAGE:

Approximately 150-200 square feet per gallon.

### LIMITATIONS:

- Do not apply when rain or high humidity is imminent.
- Not for application on general use roadways subjected to skidding tires, snowplows, or chains.
- Keep from freezing. Do not store in hot sun.
- Keep containers tightly closed when not in use.
- Do not apply when surface temperature is less than 55°F/13°C or more than 130°F/55°C.
- Allow new asphalt to cure at least 14 days
- Allow new concrete to cure no less than 28 days