

## PLSS Plexichrome Ultra Performance Sahara Sand ICP Construction Inc.

Version No: 6.8

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **08/16/2023** Print Date: **08/16/2023** S.GHS.USA.EN

#### **SECTION 1 Identification**

$D_{ra}$	A	~*	ldar	ntifier

Product name	PLSS Plexichrome Ultra Performance Sahara Sand	
Synonyms	Not Available	
Other means of identification	Not Available	

#### Recommended use of the chemical and restrictions on use

	1
Relevant identified uses	Sports Surface

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction Inc.
Address	150 Dascomb Road Andover, MA 01810 United States
Telephone	1-866-667-5119 1-978-623-9987
Fax	Not Available
Website	www.icpgroup.com
Email	sds@icpgroup.com

#### Emergency phone number

Association / Organis	tion ChemTel
Emergency telep	1-800-255-3924
Other emergency telep	one lers 1-813-248-0585

#### SECTION 2 Hazard(s) identification

## Classification of the substance or mixture NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification Carcinogenicity Category 1B, Specific Target Organ Toxicity - Repeated Exposure Category 1

#### Label elements

Hazard pictogram(s)



Signal word Dange

#### Hazard statement(s)

H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.

Version No: **6.8** Page **2** of **9** Issue Date: **08/16/2023** 

#### **PLSS Plexichrome Ultra Performance Sahara Sand**

Print Date: 08/16/2023

#### Hazard(s) not otherwise classified

Not Applicable

#### Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.

#### Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P260	Do not breathe mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

#### Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/ attention.
P314	Get medical advice/attention if you feel unwell.

#### Precautionary statement(s) Storage

P405 Store locked up.

#### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

#### **SECTION 3 Composition / information on ingredients**

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
107-21-1	0.1-1	ethylene glycol
14808-60-7*	10-30	silica crystalline - quartz
13463-67-7*	1-5	Titanium Dioxide Ti02

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

#### **SECTION 4 First-aid measures**

#### Description of first aid measures

Eye Contact	If this product comes in contact with eyes:  • Wash out immediately with water.  • If irritation continues, seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.	
Skin Contact	If skin contact occurs:  Immediately remove all contaminated clothing, including footwear.  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.	
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>	
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>	

#### Most important symptoms and effects, both acute and delayed

See Section 11

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### **SECTION 5 Fire-fighting measures**

#### **Extinguishing media**

- ► Foam.
- Dry chemical powder.

Version No: 6.8 Page 3 of 9 Issue Date: 08/16/2023

#### **PLSS Plexichrome Ultra Performance Sahara Sand**

Print Date: 08/16/2023

#### Special hazards arising from the substrate or mixture

Fire Incompatibility

▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

#### Special protective equipment and precautions for fire-fighters

#### Fire Fighting

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Combustible.
- ▶ Slight fire hazard when exposed to heat or flame.

Combustion products include: Fire/Explosion Hazard

carbon dioxide (CO2)

other pyrolysis products typical of burning organic material.

May emit poisonous fumes. May emit corrosive fumes.

#### **SECTION 6 Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

#### Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> </ul>
Major Spills	<ul> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> </ul>

contact with skin

Personal Protective Equipment advice is contained in Section 8 of the SDS.

#### **SECTION 7 Handling and storage**

#### Precautions for safe handling

	Avoid all personal contact, including inhalation.
Safe handling	Wear protective clothing when risk of exposure occurs.
	DO NOT allow clothing wet with material to stay in conta

Other information

Store in original containers. Keep containers securely sealed.

#### Conditions for safe storage, including any incompatibilities

Suitable container

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

Storage incompatibility

► Avoid reaction with oxidising agents

#### **SECTION 8 Exposure controls / personal protection**

#### **Control parameters**

#### Occupational Exposure Limits (OEL)

INGREDIENT DATA						
Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	ethylene glycol	Ethylene glycol	Not Available	Not Available	Not Available	See Appendix D
US OSHA Permissible Exposure Limits (PELs) Table Z-1	silica crystalline - quartz	Quartz - respirable	0.05 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	silica crystalline - quartz	Silica: Crystalline: Quartz (Respirable)	10 (%SiO2+2) mg/m3 / 250 (%SiO2+5) mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	silica crystalline - quartz	Silica, crystalline (as respirable dust)	0.05 mg/m3	Not Available	Not Available	Ca; See Appendix A
US OSHA Permissible Exposure Limits (PELs) Table Z-1	Titanium Dioxide Ti02	Titanium dioxide - Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Titanium Dioxide Ti02	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Titanium Dioxide Ti02	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available

Version No: **6.8** Page **4** of **9** Issue Date: **08/16/2023** 

#### PLSS Plexichrome Ultra Performance Sahara Sand

Print Date: 08/16/2023

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	Titanium Dioxide Ti02	Titanium dioxide	Not Available	Not Available	Not Available	Ca; See Appendix A
Emergency Limits						
Ingredient	TEEL-1		TEEL-2	TEEL-3		
ethylene glycol	30 ppm		150 ppm	900 ppm		

33 mg/m3

330 mg/m3

		 , ,
Ingredient	Original IDLH	Revised IDLH
ethylene glycol	Not Available	Not Available
silica crystalline - quartz	25 mg/m3 / 50 mg/m3	Not Available
Titanium Dioxide Ti02	5,000 mg/m3	Not Available

#### **Exposure controls**

silica crystalline - quartz

Titanium Dioxide Ti02

### Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

200 mg/m3

2.000 mg/m3

Individual protection measures, such as personal protective equipment



0.075 mg/m3

30 mg/m3







#### Eye and face protection

- Safety glasses with side shields.
- Chemical goggles.

Skin protection

#### See Hand protection below

### Hands/feet protection

▶ Wear chemical protective gloves, e.g. PVC.

Wear safety footwear or safety gumboots, e.g. Rubber

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### **Body protection**

#### See Other protection below

# Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent] Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type

## respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. Other protection Prior to each exit from an area containing confirmed human carcinogens, employees sh

# Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels.

- Overalls
- P.V.C apron.

#### Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Latridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

#### **SECTION 9 Physical and chemical properties**

#### Information on basic physical and chemical properties

normation on basis physical and one model properties				
Appearance	Not Available			
Physical state	Liquid	Relative density (Water = 1)	Not Available	
Odour	Not Available	Partition coefficient n-octanol / water	Not Available	
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available	
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available	
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available	
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available	

Version No: **6.8** Page **5** of **9** 

PLSS Plexichrome Ultra Performance Sahara Sand

Issue Date: **08/16/2023**Print Date: **08/16/2023** 

Flash point (°C)	>130	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	66.99

### **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

### **SECTION 11 Toxicological information**

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.  There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Еуе	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	There is ample evidence that this material can be regarded as being able to cause cancer in humans based on experiments and other information.  Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.  This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.

PLSS Plexichrome Ultra	TOXICITY	IRRITATION
Performance Sahara Sand	Not Available	Not Available
	TOXICITY	IRRITATION
	dermal (mouse) LD50: >3500 mg/kg <sup>[1]</sup>	Eye (rabbit): 100 mg/1h - mild
	Oral (Rat) LD50: >2000 mg/kg <sup>[2]</sup>	Eye (rabbit): 12 mg/m3/3D
		Eye (rabbit): 1440mg/6h-moderate
ethylene glycol		Eye (rabbit): 500 mg/24h - mild
		Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
		Skin (rabbit): 555 mg(open)-mild
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
	TOXICITY	IRRITATION
silica crystalline - quartz	Inhalation (Human)LCLo: 0.3 mg/m3/10Y <sup>[2]</sup>	Not Available

Version No: 6.8 Page 6 of 9 Issue Date: 08/16/2023

#### PLSS Plexichrome Ultra Performance Sahara Sand

Print Date: 08/16/2023

	Inhalation (Human)TCLo: 16 mppcf*/8H/17.9Y <sup>[2]</sup>		
	Inhalation (Rat)TCLo: 50 mg/m3/6H/71W <sup>[2]</sup>		
	TOXICITY	IRRITATION	
	dermal (hamster) LD50: >=10000 mg/kg <sup>[2]</sup>	Eye: no adver	se effect observed (not irritating) <sup>[1]</sup>
Titanium Dioxide Ti02	Inhalation(Rat) LC50: >2.28 mg/l4h <sup>[1]</sup>	n(Rat) LC50: >2.28 mg/l4h <sup>[1]</sup> Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
	Oral (Rat) LD50: >=2000 mg/kg <sup>[1]</sup>		
Legend:	Value obtained from Europe ECHA Registered Suspecified data extracted from RTECS - Register of Total		tained from manufacturer's SDS. Unless otherwise
ETHYLENE GLYCOL	[Estimated Lethal Dose (human) 100 ml; RTECS que For ethylene glycol: Ethylene glycol is quickly and extensively absorbed through the airways; absorption through skin is appa	throughout the gastrointestinal tract.	ctive effector in rats (birth defects). Mutagenic to rat cell Limited information suggests that it is also absorbed
silica crystalline - quartz		ARC) has classified occupational exp d on what IARC considered sufficient	
silica crystalline - quartz  Acute Toxicity	The International Agency for Research on Cancer (I/carcinogenic to humans . This classification is based	ARC) has classified occupational exp d on what IARC considered sufficient	oosures to <b>respirable</b> (<5 um) crystalline silica as being
	The International Agency for Research on Cancer (II carcinogenic to humans . This classification is based the carcinogenicity of inhaled silica in the forms of qu	ARC) has classified occupational exp d on what IARC considered sufficient uartz and cristobalite.	oosures to <b>respirable</b> (<5 um) crystalline silica as being evidence from epidemiological studies of humans for
Acute Toxicity Skin Irritation/Corrosion	The International Agency for Research on Cancer (I/carcinogenic to humans . This classification is based the carcinogenicity of inhaled silica in the forms of qu	ARC) has classified occupational exp d on what IARC considered sufficient uartz and cristobalite.  Carcinogenicity	oosures to <b>respirable</b> (<5 um) crystalline silica as being evidence from epidemiological studies of humans for
Acute Toxicity	The International Agency for Research on Cancer (I/carcinogenic to humans . This classification is based the carcinogenicity of inhaled silica in the forms of qu	ARC) has classified occupational exp d on what IARC considered sufficient uartz and cristobalite.  Carcinogenicity  Reproductivity	posures to <b>respirable</b> (<5 um) crystalline silica as being evidence from epidemiological studies of humans for

✓ – Data available to make classification

### **SECTION 12 Ecological information**

#### Toxicity

	Endpoint	Test Duration (hr)	Species	Valu	e	Source
Performance Sahara Sand	Not Available	Not Available	Not Available	Not Avai	Available   Value   6500-13000mg/l   >100mg/l   8050mg/l   6500-7500mg/l   Value   Not Available   Value   <1.1-9.6   3.75-7.58mg/l	Not Available
	Endpoint	Test Duration (hr)	Species	Value		Source
	EC50	96h	Algae or other aquatic plants	6500-1300	00mg/l	1
erformance Sahara Sand ethylene glycol	EC50	48h	Crustacea	Crustacea >100mg/l		2
	LC50	96h	Fish	8050mg/l		4
	EC50(ECx)	Not Available	Algae or other aquatic plants	6500-7500	Omg/I	1
	Endpoint	Test Duration (hr)	Species	Species Value		Source
silica crystalline - quartz	Not Available	Not Available	Not Available		Value	Not Available
	Endpoint	Test Duration (hr)	Species	Value		Source
ethylene glycol silica crystalline - quartz	BCF	1008h	Fish	<1.1-9.6	<1.1-9.6	
	EC50	72h	Algae or other aquatic plants	3.75-7.5	58mg/l	4
ethylene glycol silica crystalline - quartz Titanium Dioxide Ti02	EC50	48h	Crustacea	1.9mg/l		2
	EC50	96h	Algae or other aquatic plants	179.05r	ng/l	2
	LC50	96h	Fish	1.85-3.0	06mg/l	4
	NOEC(ECx)	672h	Fish	>=0.004	4mg/L	2
Legend:			CHA Registered Substances - Ecotoxicological Inf C Aquatic Hazard Assessment Data 6. NITE (Japa			

#### DO NOT discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethylene glycol	LOW (Half-life = 24 days)	LOW (Half-life = 3.46 days)
Titanium Dioxide Ti02	HIGH	HIGH

Version No: 6.8 Page 7 of 9 Issue Date: 08/16/2023 Print Date: 08/16/2023

#### PLSS Plexichrome Ultra Performance Sahara Sand

Ingredient	Bioaccumulation
ethylene glycol	LOW (BCF = 200)
Titanium Dioxide Ti02	LOW (BCF = 10)

#### Mobility in soil

Ingredient	Mobility
ethylene glycol	HIGH (KOC = 1)
Titanium Dioxide Ti02	LOW (KOC = 23.74)

#### **SECTION 13 Disposal considerations**

#### Waste treatment methods

- Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible

#### Product / Packaging disposal

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- Recycle wherever possible or consult manufacturer for recycling options.
- ► Consult State Land Waste Authority for disposal.

#### **SECTION 14 Transport information**

#### Labels Required

**Marine Pollutant** NO

Shipping container and transport vehicle placarding and labeling may vary from the below information. Products that are regulated for transport will be packaged and marked as Dangerous Goods in Limited Quantities according to US DOT, IATA and IMDG regulations. In case of reshipment, it is the responsibility of the shipper to determine the appropriate

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

labels and markings in accordance with applicable transport regulations.

Not Applicable

#### Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

•	
Product name	Group
ethylene glycol	Not Available
silica crystalline - quartz	Not Available
Titanium Dioxide Ti02	Not Available

#### Transport in bulk in accordance with the IGC Code

Product name	Ship Type
ethylene glycol	Not Available
silica crystalline - quartz	Not Available
Titanium Dioxide Ti02	Not Available

#### **SECTION 15 Regulatory information**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

#### ethylene glycol is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US - California Proposition 65 - Maximum Allowable Dose Levels (MADLs) for

Chemicals Causing Reproductive Toxicity

US - California Proposition 65 - Reproductive Toxicity

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)

silica crystalline - quartz is found on the following regulatory lists

US Clean Air Act - Hazardous Air Pollutants

US DOE Temporary Emergency Exposure Limits (TEELs)

US EPA Integrated Risk Information System (IRIS)

US EPCRA Section 313 Chemical List

US NIOSH Recommended Exposure Limits (RELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Version No: 6.8 Issue Date: 08/16/2023 Page 8 of 9

#### PLSS Plexichrome Ultra Performance Sahara Sand

Print Date: 08/16/2023

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

## Titanium Dioxide Ti02 is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

US - California Proposition 65 - Carcinogens

 $\ensuremath{\mathsf{US}}$  - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US National Toxicology Program (NTP) 15th Report Part A Known to be Human

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Carcinogens Listing

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### **Federal Regulations**

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Section 311/312 hazard categories

Oction 31 7/312 nazara categories	
Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
n contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	Yes
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	

#### US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg	
ethylene glycol	5000	2270	

#### **State Regulations**

#### US. California Proposition 65



MARNING: This product can expose you to chemicals including silica crystalline - quartz, Titanium Dioxide Ti02, which are known to the State of California to cause cancer, and ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

#### **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (ethylene glycol; silica crystalline - quartz; Titanium Dioxide Ti02)

Version No: **6.8** Page **9** of **9** Issue Date: **08/16/2023** 

#### PLSS Plexichrome Ultra Performance Sahara Sand

Print Date: **08/16/2023** 

National Inventory	Status
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

#### **SECTION 16 Other information**

Revision Date	08/16/2023
Initial Date	02/14/2021

#### CONTACT POINT

\*\*PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES\*\*

#### **SDS Version Summary**

Version	Date of Update	Sections Updated
5.8	08/16/2023	Composition / information on ingredients - Ingredients

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

#### **Definitions and abbreviations**

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit₀

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value BCF: BioConcentration Factors

BEI: Biological Exposure Index

BEI: Biological Exposure Index
AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.