

REBOUND LINEMARKING

Available in White, Yellow, Blue & Red

APPLICATION PROCEDURE

Description:

Rebound Linemarking is a high opacity water based acrylic coating suitable for linemarking on all water based Rebound Topcoat surfaces. It is specially designed to have the same slip and play characteristics as the court surface.

Rebound Linemarking can be applied by brush, spray or mini-roller. International Tennis Standards Linemarking Specification is for white 50 mm width lines. For spray application it can be diluted up to 10 % with water where required.

For high definition lines with “sharp” edges, **CSS Line Rite** can be used in conjunction with conventional tape systems.

CSS Line Rite:

CSS Line Rite is a 100% acrylic clear sealer used to seal taped edges when linemarking to produce a clean crisp line edge.

Application Procedure:

1. Prior to applying line marking, make sure the topcoat surface is clean and free from dust and loose material.
2. Mark out court lines using a chalked string line.
3. Apply tape using a tape machine ensuring lines are straight and the tape is compressed to achieve good contact with the topcoat surface.
4. Apply **CSS Line Rite** directly from the container. Using a paint brush or mini-roller, apply over the tape edge to seal the edge to minimise any bleed under the tape when applying the white line marking coating.
5. Allow sealer to cure. The sealer will be clear when cured and can take from 10-30 minutes depending on ambient conditions.
6. Apply the White line marking paint by brush or mini-roller being careful to stay within the tape and avoid spillage onto the play area.
7. Allow line marking to dry then remove tape.

NB The use of **CSS Line Rite** is optional and is used to produce a crisp line edge.

Coverage:

Rebound Linemarking: 2 to 3 litres [.53 - .8 gal] per standard tennis court

CSS Line Rite: 1 to 2 litres per standard tennis court [.26 - .53 gal]

Important: The information, and the recommendations relating to the application/s and end use of California Sports Surfaces Products, are given in good faith based on California Sports Surfaces current knowledge and experience of the products when properly stored, handled, and applied in normal conditions. In practice, the differences in substrates, materials and actual site conditions are such that no warranty in respect of the merchantability or of suitability for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. Users should always refer to the most recent issue of the Australian version of the Technical Bulletin for the product concerned, copies of which are supplied on request.

PLEASE CONSULT TECHNICAL DEPARTMENT FOR PRODUCT RECOMMENDATIONS AND ADVICE. PRE-TESTING OF SUBSTRATES IS RECOMMENDED TO ENSURE PERFORMANCE OF PRODUCT UNDER ALL CONDITIONS.