

ICP Group Australasia Pty Ltd

Version No: 5.8

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Issue Date: 10/17/2022 Print Date: 10/17/2022 S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	CoolTop Multisport All Colors
Synonyms	Not Available
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Sports Surface

Details of the manufacturer or supplier of the safety data sheet

Registered company name	ICP Group Australasia Pty Ltd	ICP Construction Inc.
Address	30-32 Assembly Drive Tullamarine, VIC 3043 Australia 150 Dascomb Road Andover, MA 01810 United States	
Telephone	61 3 9338 9851	1-866-667-5119 1-978-623-9987
Fax Not Available Not Available		Not Available
Website	www.icpgroup.com	www.icpgroup.com
Email	sales-australia@icpgroup.com	sds@icpgroup.com

Emergency telephone number

Association / Or	ganisation	ChemTel	ChemTel
Emergency	telephone numbers	1300-954-583	1-800-255-3924
Other emergency	telephone numbers	Not Available	1-813-248-0585

SECTION 2 Hazards identification

Classification of the substance or mixture	Classification	f the substance	or mixture
--	-----------------------	-----------------	------------

Poisons Schedule	Not Applicable
Classification ^[1]	Carcinogenicity Category 1A, Serious Eye Damage/Eye Irritation Category 2B, Specific Target Organ Toxicity - Repeated Exposure Category 1
Legend:	1. Classified by Chernwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements



Signal word

Hazard statement(s)

H350	May cause cancer.	
H320	Causes eye irritation.	
H372	Causes damage to organs through prolonged or repeated exposure.	

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P260	Do not breathe mist/vapours/spray.

P280	Wear protective gloves and protective clothing.	
P270	o not eat, drink or smoke when using this product.	
P202	o not handle until all safety precautions have been read and understood.	
P264	Wash all exposed external body areas thoroughly after handling.	
P272	P272 Contaminated work clothing must not be allowed out of the workplace.	

Precautionary statement(s) Response

recontionary statement(s) response		
P308+P313	IF exposed or concerned: Get medical advice/ attention.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P314	Get medical advice/attention if you feel unwell.	
P337+P313	If eye irritation persists: Get medical advice/attention.	

Precautionary statement(s) Storage

P405 Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight] Name		
13463-67-7*	0.1-1	1-1 <u>Titanium Dioxide</u>	
107-21-1	-5 ethylene glycol		
14808-60-7*	30-60 <u>Silica Chrystalline - Quartz</u>		
13983-17-0	1-5 wollastonite		
330-54-1	<0.1 diuron		
Legend:	end: 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available		

SECTION 4 First aid measures

Description of first aid measures	
Eye Contact	 If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

for diuron:

- Symptomatic and supportive action is indicated.
- Methaemoglobinaemia is possible
- if compound is hydrolysed in vivo to aniline.
- Methaemoglobinaemia causes cyanosis. Reversion of methaemoglobin to haemoglobin is spontaneous after removal from exposure, so moderate degrees of cyanosis need be

treated only by supportive measures such as bed rest and oxygen inhalation.

Thorough cleansing of the entire contaminated area of the body, including the scalp and nails is of the utmost importance.

SECTION 5 Firefighting measures

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result		
Advice for firefighters			
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. 		
Fire/Explosion Hazard	carbon dioxide (CO2) other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes.		
HAZCHEM	Not Applicable		

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling Safe handling • Avoid all personal contact, including inhalation. • Wear protective clothing when risk of exposure occurs. • Use in a well-ventilated area. • DO NOT allow clothing wet with material to stay in contact with skin

Conditions for safe storage, including any incompatibilities

Suitable container	 Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	Titanium Dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	 (a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Australia Exposure Standards	ethylene glycol	Ethylene glycol (vapour)	20 ppm / 52 mg/m3	104 mg/m3 / 40 ppm	Not Available	Not Available
Australia Exposure Standards	ethylene glycol	Ethylene glycol (particulate)	10 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	Silica Chrystalline - Quartz	Silica - Crystalline: Quartz (respirable dust)	0.05 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	diuron	Diuron	10 mg/m3	Not Available	Not Available	Not Available

Ingredient	TEEL-1	TEEL-2	TEEL-3
Titanium Dioxide	30 mg/m3	330 mg/m3	2,000 mg/m3

Ingredient	TEEL-1	TEEL-2		TEEL-3	
ethylene glycol	30 ppm	150 ppm		900 ppm	
Silica Chrystalline - Quartz	0.075 mg/m3	33 mg/m3		200 mg/m3	
Ingredient	Original IDLH		Revised	IDLH	
Titanium Dioxide	•		Not Avai	Not Available	
ethylene glycol	Not Available		Not Available		
Silica Chrystalline - Quartz	25 mg/m3 / 50 mg/m3		Not Avai	lable	
wollastonite	Not Available	Not Available		lable	
diuron	Not Available		Not Avai	lable	

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls ca be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk.
Personal protection	
Eye and face protection	 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.
Body protection	See Other protection below
Other protection	 Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent] Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted. Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. Overalls. P.V.C apron. Barrier cream.

Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Modified cellulose polymers formed by the reaction with the free hydroxyl groups in cellulose. The number of hydroxyl groups reacting, as well as the the nature of the substituent, largely determine the physical properties, particularly solubility, of the product.			
Physical state	Liquid	Relative density (Water = 1)	Not Available	
Odour	Not Available	Partition coefficient n-octanol / water	Not Available	

Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (Not Available%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	35

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

•	
Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Strong evidence exists that this substance may cause irreversible mutations (though not lethal) even following a single exposure. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. There is sufficient evidence to suggest that this material directly causes cancer in humans. Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects. Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility. Red blood cells and rabbit alveolar macrophages exposed to calcium silicate insulation materials in vitro showed haemolysis in one study but not in another. Both studies showed the substance to be more cytotoxic than titanium dioxide but less toxic than asbestos. In a small cohort mortality study of workers in a wollastonite quarry, the observed number of deaths from all cancers combined and lung cancer were lower than expected. According to animal testing, wollastonite only caused a small increase in sarcomas of the chest cavity. A study of workers in a wollastonite quarry showed that deaths from all cancers were lower than expected. Occupational exposure can cuase reduced lung function and lung disease. Chronic effects of exposure to diuron may include skin irritation, abnormal pigmentation, growth retardation, blurring of vision, abnormal liver, spleen and thyroid effects; red blood cell destruction, or reduction of the blood's oxygen carrying capacity causing bluish discolouration and breathlessness.

CoolTon Multisnort All Colors	ΤΟΧΙΟΙΤΥ	IRRITATION			
CoolTop Multisport All Colors	Not Available	Not Available			
	тохісіту	IRRITATION			
	dermal (hamster) LD50: >=10000 mg/kg ^[2]	Eye: no adverse	effect observed (not irritating) ^[1]		
Titanium Dioxide	Inhalation(Rat) LC50; >2.28 mg/l4h ^[1]	Skin: no adverse	e effect observed (not irritating) ^[1]		
	Oral (Rat) LD50; >=2000 mg/kg ^[1]				
	ΤΟΧΙΟΙΤΥ	IRRITATION			
	dermal (mouse) LD50: >3500 mg/kg ^[1]	Eye (rabbit): 100) mg/1h - mild		
	Oral (Rat) LD50; >2000 mg/kg ^[2]	Eye (rabbit): 12	mg/m3/3D		
		Eye (rabbit): 144	10mg/6h-moderate		
ethylene glycol		Eye (rabbit): 500 mg/24h - mild			
		Eye: no adverse	effect observed (not irritating) ^[1]		
		Skin (rabbit): 55			
			e effect observed (not irritating) ^[1]		
	ΤΟΧΙΟΙΤΥ	IRRITATION			
Silica Chrystalline - Quartz	Oral (Rat) LD50; 500 mg/kg ^[2]	Not Available			
	ΤΟΧΙΟΙΤΥ	IRRITATION			
wollastonite	Not Available	Not Available			
	ΤΟΧΙΟΙΤΥ	IRRITATION			
	dermal (rat) LD50: >2000 mg/kg ^[1]		se effect observed (not irritating) ^[1]		
diuron	Inhalation(Rat) LC50; >5.05 mg/l4h ^[1]		e effect observed (not irritating) ^[1]		
	Oral (Rat) LD50; 1017 mg/kg ^[2]				
Legend:	1. Value obtained from Europe ECHA Registered Sul	bstances - Acute toxicity 2. Value obta	ined from manufacturer's SDS. Unless otherwise		
	specified data extracted from RTECS - Register of To	oxic Effect of chemical Substances			
CoolTop Multisport All Colors	Laboratory (in vitro) and animal studies show, expose producing mutation. The following information refers to contact allergens a Contact allergies quickly manifest themselves as con eczema involves a cell-mediated (T lymphocytes) imr	as a group and may not be specific to t tact eczema, more rarely as urticaria o	this product.		
ETHYLENE GLYCOL	[Estimated Lethal Dose (human) 100 ml; RTECS quo For ethylene glycol: Ethylene glycol is quickly and extensively absorbed th through the airways; absorption through skin is appar	nroughout the gastrointestinal tract. Lir	nited information suggests that it is also absorbed		
WOLLASTONITE	The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or lim	ited in animal testing.			
DIURON	Note: Equivocal animal tumorigenic agent by RTECS tetrachloroazoxybenzene). Maximum impurity levels a				
CoolTop Multisport All Colors & DIURON	Diuron is absorbed readily through the gut and lungs, are more susceptible than adults. Exposure to sublet haemoglobin which carries oxygen in the blood.				
WOLLASTONITE & DIURON	No significant acute toxicological data identified in lite	rature search.			
Acute Toxicity	×	Carcinogenicity	✓		
Skin Irritation/Corrosion	×	Reproductivity	×		
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	×		
Respiratory or Skin	×	STOT - Repeated Exposure			
sensitisation					

SECTION 12 Ecological information

Image: Second second

BCF EC50 EC50	1008h 72h	Fish Algae or other aquatic plants	<1.1-9.6	-	7
EC50		Algae or other aquatic plants			
			3.75-7.58mg/l		4
	48h	Crustacea	1.9mg/l		2
NOEC(ECx)	504h	Crustacea	a 0.02mg/l		4
LC50	96h	Fish	1.85-3.06mg/l		4
EC50	96h	Algae or other aquatic plants	179.05r	ng/l	2
Endpoint	Test Duration (hr)	Species	Value		Sourc
EC50(ECx)	Not Available	Algae or other aquatic plants	6500-7500)mg/l	1
EC50	48h	Crustacea	>100mg/l		2
LC50	96h	Fish	>10000mg	g/l	1
EC50	96h	Algae or other aquatic plants	Algae or other aquatic plants 6500-13000mg		1
Endpoint	Test Duration (hr)	Species	Species Value		Source
Not Available	Not Available	Not Available	Not Avai	lable	Not Availab
Endpoint	Test Duration (hr)	Species	Species Value		Source
Not Available	Not Available	Not Available	Not Avai	lable	Not Availab
Endpoint	Test Duration (hr)	Species	Value		Sourc
BCF	1008h	Fish	<2.9-14		7
EC50	72h	Algae or other aquatic plants	0.004m	g/L	4
EC50	48h	Crustacea	acea 1-1.9mg/l		4
LC50	96h	Fish	0.53-0.9	96mg/l	4
NOEC(ECx)	2h	Algae or other aquatic plants	<0.001mg/L		4
EC50	96h	Algae or other aquatic plants	0.001m	g/I	4
	Endpoint EC50(ECx) EC50(ECx) EC50 EC50 EC50 EC50 EC50 EC50 EC50 EC50	EndpointTest Duration (hr)EC50(ECx)Not AvailableEC5048hLC5096hEC5096hEC5096hEC50Not AvailableEndpointTest Duration (hr)Not AvailableNot AvailableEndpointTest Duration (hr)Not AvailableNot AvailableEndpointTest Duration (hr)BCF1008hEC5072hEC5048hLC5096hNOEC(ECx)2hEC5096h	EndpointTest Duration (hr)SpeciesEC50(ECx)Not AvailableAlgae or other aquatic plantsEC5048hCrustaceaLC5096hFishEC5096hAlgae or other aquatic plantsEC5096hNot aquatic plantsEC5096hNot aquatic plantsEndpointTest Duration (hr)SpeciesNot AvailableNot AvailableNot AvailableNot AvailableNot AvailableNot AvailableNot AvailableTest Duration (hr)SpeciesEndpointTest Duration (hr)SpeciesNot AvailableNot AvailableNot AvailableNot AvailableNot AvailableNot AvailableEc501008hFishEC5072hAlgae or other aquatic plantsEC5096hFishNOEC(ECX)2hAlgae or other aquatic plantsEC5096hAlgae or other aquatic plants	Endpoint Test Duration (hr) Species Value EC50(ECx) Not Available Algae or other aquatic plants 6500-7500 EC50 48h Crustacea >1000ng/l LC50 96h Fish >10000mg EC50 96h Algae or other aquatic plants 6500-7500 EC50 96h Fish >10000mg EC50 96h Algae or other aquatic plants 6500-1300 Endpoint Test Duration (hr) Species Value Not Available Not Available Not Available Not Available Endpoint Test Duration (hr) Species Value Ec50 Test Duration (hr) Species Value BCF 1008h Fish <2.9-14	Image: Problem intermediate intermedia

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites. For Diuron: Vapor pressure: 6.90 x10-8 mm Hg (25 C); Henry's law constant: 5.10 x 10-10 atm m3 mol-1. Atmospheric Fate: Diuron is non-volatile in the atmosphere and is unlikely to be dispersed over large areas. Diuron has a low tendency to volatilize from water or moist soils. DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air	
Titanium Dioxide	HIGH	HIGH	
ethylene glycol	LOW (Half-life = 24 days)	LOW (Half-life = 3.46 days)	
diuron	HIGH	HIGH	

Bioaccumulative potential

Ingredient	Bioaccumulation
Titanium Dioxide	LOW (BCF = 10)
ethylene glycol	LOW (BCF = 200)
diuron	LOW (BCF = 14)

Mobility in soil

Ingredient	Mobility
Titanium Dioxide	LOW (KOC = 23.74)
ethylene glycol	HIGH (KOC = 1)
diuron	LOW (KOC = 136)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

- Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Continued...

 Otherwise: If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sever may be subject to local laws and regulations and these should be considered first. Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or
 disposal facility can be identified. Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material).
apparates (and admixture with suitable compusible matchal).

SECTION 14 Transport information

Labels Required	
Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
Titanium Dioxide	Not Available
ethylene glycol	Not Available
Silica Chrystalline - Quartz	Not Available
wollastonite	Not Available
diuron	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
Titanium Dioxide	Not Available
ethylene glycol	Not Available
Silica Chrystalline - Quartz	Not Available
wollastonite	Not Available
diuron	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

Titanium Dioxide is found on the following regulatory lists		
Australian Inventory of Industrial Chemicals (AIIC)	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	
Chemical Footprint Project - Chemicals of High Concern List	Monographs - Group 2B: Possibly carcinogenic to humans	
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)	
ethylene glycol is found on the following regulatory lists		
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -	
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -	Schedule 6	
Schedule 5	Australian Inventory of Industrial Chemicals (AIIC)	
	Chemical Footprint Project - Chemicals of High Concern List	
Silica Chrystalline - Quartz is found on the following regulatory lists		
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	Chemical Footprint Project - Chemicals of High Concern List	
Australia Model Work Health and Safety Regulations - Hazardous chemicals (other than lead) requiring health monitoring	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	
Australian Inventory of Industrial Chemicals (AIIC)	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans	
welle stanite is found on the following angulaton. Boto		
wollastonite is found on the following regulatory lists		
Australian Inventory of Industrial Chemicals (AIIC)	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	

diuron is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australian Inventory of Industrial Chemicals (AIIC) Chemical Footprint Project - Chemicals of High Concern List International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (Titanium Dioxide; ethylene glycol; Silica Chrystalline - Quartz; wollastonite; diuron)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	10/17/2022
Initial Date	10/06/2022

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

SDS Version Summary

Version	Date of Update	Sections Updated
4.8	10/17/2022	Acute Health (eye), Classification, Fire Fighter (fire/explosion hazard), First Aid (eye), Ingredients, Physical Properties

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.

Powered by AuthorITe, from Chemwatch.