

Line Paint Textured White - 6220 ICP Construction Inc.

Version No: 4.8

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: 10/17/2022 Print Date: 10/17/2022 S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	Line Paint Textured White - 6220	
Synonyms	Not Available	
Other means of identification	Not Available	

Recommended use of the chemical and restrictions on use

Relevant identified uses	Line Paint

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction Inc.	
Address	50 Dascomb Road Andover, MA 01810 United States	
Telephone	66-667-5119 1-978-623-9987	
Fax	Not Available	
Website	www.icpgroup.com	
Email	sds@icpgroup.com	

Emergency phone number

Association / Organis	tion ChemTel
Emergency telep	1-800-255-3924
Other emergency telep	one lers 1-813-248-0585

SECTION 2 Hazard(s) identification

Classification of the substance or mixture NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Carcinogenicity Category 1B, Specific Target Organ Toxicity - Repeated Exposure Category 1

Label elements

Hazard pictogram(s)



Signal word

Dange

Hazard statement(s)

H350	May cause cancer.	
H372	Causes damage to organs through prolonged or repeated exposure.	

Version No: **4.8** Page **2** of **10** Issue Date: **10/17/2022**

Line Paint Textured White - 6220

Print Date: 10/17/2022

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read label before use.	

Precautionary statement(s) Prevention

P260	Do not breathe mist/vapours/spray.	
P280	Wear protective gloves and protective clothing.	
P270	o not eat, drink or smoke when using this product.	
P202	Do not handle until all safety precautions have been read and understood.	
P264	Wash all exposed external body areas thoroughly after handling.	

Precautionary statement(s) Response

	·
P308+P313	IF exposed or concerned: Get medical advice/ attention.
P314	Get medical advice/attention if you feel unwell.

Precautionary statement(s) Storage

P405 Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name	
14808-60-7*	10-30	silica crystalline - quartz	
12001-26-2	1-5	mica	
13463-67-7*	10-30	titanium dioxide	
107-21-1	1-5	ethylene glycol	

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: • Wash out immediately with water. • If irritation continues, seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Fire-fighting measures

Extinguishing media

► Foam.

Version No: 4.8 Page 3 of 10 Issue Date: 10/17/2022 Print Date: 10/17/2022

Line Paint Textured White - 6220

Dry chemical powder.

Special hazards arising from the substrate or mixture

Fire Incompatibility

▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Special protective equipment and precautions for fire-fighters

Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.

Slight fire hazard when exposed to heat or flame.

Fire/Explosion Hazard

Combustion products include:

carbon dioxide (CO2)

Combustible.

other pyrolysis products typical of burning organic material.

May emit corrosive fumes.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Remove all ignition sources.Clean up all spills immediately.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions	for	safe	handling

Safe	hand	ling
		-

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.

► DO NOT allow clothing wet with material to stay in contact with skin

- Other information
- Store in original containers.
- Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

Storage incompatibility

Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INCREDIENT DATA

INGREDIENT DATA						
Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-1	silica crystalline - quartz	Quartz - respirable	0.05 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	silica crystalline - quartz	Silica: Crystalline: Quartz (Respirable)	10 (%SiO2+2) mg/m3 / 250 (%SiO2+5) mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	silica crystalline - quartz	Silica, crystalline (as respirable dust)	0.05 mg/m3	Not Available	Not Available	Ca; See Appendix A
US OSHA Permissible Exposure Limits (PELs) Table Z-1	mica	Particulates Not Otherwise Regulated (PNOR)- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	mica	Particulates Not Otherwise Regulated (PNOR)- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	mica	Silicates (less than 1% crystalline silica): Mica	20 mppcf	Not Available	Not Available	Not Available

Version No: 4.8 Page 4 of 10 Issue Date: 10/17/2022 Print Date: 10/17/2022

Line Paint Textured White - 6220

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	mica	Mica (containing less than 1% quartz)	3 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	titanium dioxide	Titanium dioxide - Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	titanium dioxide	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	titanium dioxide	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	titanium dioxide	Titanium dioxide	Not Available	Not Available	Not Available	Ca; See Appendix A
US NIOSH Recommended Exposure Limits (RELs)	ethylene glycol	Ethylene glycol	Not Available	Not Available	Not Available	See Appendix

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
silica crystalline - quartz	0.075 mg/m3	33 mg/m3	200 mg/m3
mica	9 mg/m3	99 mg/m3	590 mg/m3
titanium dioxide	30 mg/m3	330 mg/m3	2,000 mg/m3
ethylene glycol	30 ppm	150 ppm	900 ppm

Ingredient	Original IDLH	Revised IDLH
silica crystalline - quartz	25 mg/m3 / 50 mg/m3	Not Available
mica	1,500 mg/m3	Not Available
titanium dioxide	5,000 mg/m3	Not Available
ethylene glycol	Not Available	Not Available

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

Personal protection









Eye and face protection

- Safety glasses with side shields.
- Chemical goggles.

Skin protection

See Hand protection below

- ▶ Wear chemical protective gloves, e.g. PVC.
- Hands/feet protection

Wear safety footwear or safety gumboots, e.g. Rubber

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Body protection

See Other protection below

Other protection

- Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent]
- Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type
- respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable
- labels. Overalls
- P.V.C apron.

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance

Not Available

Version No: 4.8 Page **5** of **10** Issue Date: 10/17/2022 Print Date: 10/17/2022

Line Paint Textured White - 6220

Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (Not Available%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

silica crystalline - quartz

formation on toxicological e	ffects				
Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.				
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.				
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.				
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).				
Chronic	There is sufficient evidence to suggest that this material directly causes cancer in humans. Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.				
Line Paint Textured White -	TOXICITY	IRRITATION			
6220	Not Available	Not Available			
	TOXICITY	IRRITATION			
	Inhalation (Human)LCLo: 0.3 mg/m3/10Y ^[2] Not Available				

Inhalation (Human)TCLo: 16 mppcf*/8H/17.9Y^[2] Inhalation (Rat)TCLo: 50 mg/m3/6H/71W $^{[2]}$

Version No: 4.8 Page 6 of 10 Issue Date: 10/17/2022 Print Date: 10/17/2022

IRRITATION

Line Paint Textured White - 6220

TOXICITY

	Not Available	Not Available		
	TOXICITY	IRRITATION		
	Inhalation (Rat)TCLo: 0.04 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]		
	Oral (Mouse)LD50; >10000 mg/kg * ^[2]	Skin (human): 0.3 mg /3D (int)-mild *		
titanium dioxide	Oral (Mouse)TDLo: 0.0032 mg/kg ^[2]	Skin: no adverse effect observed (not irritating) ^[1]		
	Oral (Rat)LD50; >20000 mg/kg *[2]			
	Oral (Rat)TDLo: 60000 mg/kg ^[2]			
	TOXICITY	IRRITATION		
	dermal (mouse) LD50: >3500 mg/kg ^[1]	Eye (rabbit): 100 mg/1h - mild		
	Oral (Rat) LD50; >2000 mg/kg ^[2]	Eye (rabbit): 12 mg/m3/3D		
ethylene glycol		Eye (rabbit): 1440mg/6h-moderate		
etitylerie glycol		Eye (rabbit): 500 mg/24h - mild		
		Eye: no adverse effect observed (not irritating) ^[1]		
		Skin (rabbit): 555 mg(open)-mild		
		Skin: no adverse effect observed (not irritating) ^[1]		
Legend:	Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances			
	WARNING: For inhalation exposure ONLY: This substance has been c	lassified by the IARC as Group 1: CARCINOGENIC TO HUMANS		
silica crystalline - quartz	The International Agency for Research on Cancer (IARC) has classified occupational exposures to respirable (<5 um) crystalline silica as being carcinogenic to humans. This classification is based on what IARC considered sufficient evidence from epidemiological studies of humans for the carcinogenicity of inhaled silica in the forms of quartz and cristobalite.			
titanium dioxide	* IUCLID Laboratory (in vitro) and animal studies show, exposure to the material may result in a possible risk of irreversible effects, with the possibility of producing mutation. Exposure to titanium dioxide is via inhalation, swallowing or skin contact. When inhaled, it may deposit in lung tissue and lymph nodes causing dysfunction of the lungs and immune system. The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.			

ETHYLENE GLYCOL

[Estimated Lethal Dose (human) 100 ml; RTECS quoted by Orica] Substance is reproductive effector in rats (birth defects). Mutagenic to rat cells. For ethylene glycol:

Ethylene glycol is quickly and extensively absorbed throughout the gastrointestinal tract. Limited information suggests that it is also absorbed through the airways; absorption through skin is apparently slow.

MICA & titanium dioxide

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. No significant acute toxicological data identified in literature search.

Acute Toxicity	×	Carcinogenicity	✓
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	✓
Mutagenicity	×	Aspiration Hazard	×

Legend:

 ★ – Data either not available or does not fill the criteria for classification
 → Data available to make classification - Data available to make classification

SECTION 12 Ecological information

Toxicity

Line Deint Tentuned White	Endpoint	Test Duration (hr)	Species	Value S	Source
Line Paint Textured White - 6220	Not Available	Not Available	Not Available		Not Available
silica crystalline - quartz	Endpoint	Test Duration (hr)	Species	Value S	Source
	Not Available	Not Available	Not Available		Not Availabl
	Endpoint	Test Duration (hr)	Species	Value S	Source
mica					

Version No: 4.8 Page 7 of 10 Issue Date: 10/17/2022 Print Date: 10/17/2022

Line Paint Textured White - 6220

	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	BCF	1008h	Fish	<1.1-9.6	7
	EC50	72h	Algae or other aquatic plants	3.75-7.58mg/l	4
titanium dioxide	EC50	48h	Crustacea	1.9mg/l	2
	NOEC(ECx)	504h	Crustacea	0.02mg/l	4
	LC50	96h	Fish	1.85-3.06mg/l	4
	EC50	96h	Algae or other aquatic plants	179.05mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	Not Available	Algae or other aquatic plants	6500-7500mg/l	1
ethylene glycol	EC50	48h	Crustacea	>100mg/l	2
	LC50	96h	Fish	>10000mg/l	1
	EC50	96h	Algae or other aquatic plants	6500-13000mg/l	1
Legend:			CHA Registered Substances - Ecotoxicological Info C Aquatic Hazard Assessment Data 6. NITE (Japan		

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
titanium dioxide	HIGH	HIGH
ethylene glycol	LOW (Half-life = 24 days)	LOW (Half-life = 3.46 days)

Bioaccumulative potential

Ingredient	Bioaccumulation	
titanium dioxide	LOW (BCF = 10)	
ethylene glycol	LOW (BCF = 200)	

Mobility in soil

Ingredient	Mobility	
titanium dioxide	LOW (KOC = 23.74)	
ethylene glycol	HIGH (KOC = 1)	

SECTION 13 Disposal considerations

Waste treatment methods

- Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

Product / Packaging disposal

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal. Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.

SECTION 14 Transport information

Labels Required

Marine Pollutant NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
silica crystalline - quartz	Not Available

Line Paint Textured White - 6220

Product name	Group
mica	Not Available
titanium dioxide	Not Available
ethylene glycol	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
silica crystalline - quartz	Not Available
mica	Not Available
titanium dioxide	Not Available
ethylene glycol	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

silica crystalline - quartz is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

US National Toxicology Program (NTP) 15th Report Part A Known to be Human Carcinogens

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Carcinogens Listing

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

mica is found on the following regulatory lists

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

titanium dioxide is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US TSCA Chemical Substance Inventory - Interim List of Active Substances

ethylene glycol is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US - California Proposition 65 - Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity`

US - California Proposition 65 - Reproductive Toxicity

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)

US Clean Air Act - Hazardous Air Pollutants

US DOE Temporary Emergency Exposure Limits (TEELs)

US EPA Integrated Risk Information System (IRIS)

US EPCRA Section 313 Chemical List

US NIOSH Recommended Exposure Limits (RELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No

Version No: 4.8 Page 9 of 10 Issue Date: 10/17/2022 Print Date: 10/17/2022

Line Paint Textured White - 6220

No Corrosive to metal Oxidizer (Liquid, Solid or Gas) No Organic Peroxide No Self-reactive No In contact with water emits flammable gas No Combustible Dust No Carcinogenicity Yes Acute toxicity (any route of exposure) No Reproductive toxicity No Skin Corrosion or Irritation No Respiratory or Skin Sensitization No Serious eye damage or eye irritation No Specific target organ toxicity (single or repeated exposure) Yes Aspiration Hazard Nο Germ cell mutagenicity No Simple Asphyxiant Nο Hazards Not Otherwise Classified No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
ethylene glycol	5000	2270

State Regulations

US. California Proposition 65



MARNING: This product can expose you to chemicals including silica crystalline - quartz, titanium dioxide, which are known to the State of California to cause cancer, and ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnin

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (silica crystalline - quartz; mica; titanium dioxide; ethylene glycol)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (mica)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	No (mica)
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	10/17/2022
Initial Date	10/10/2022

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

SDS Version Summary

Version	Date of Update	Sections Updated
3.8	10/17/2022	Ingredients, Physical Properties, Name

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

Version No: **4.8** Page **10** of **10** Issue Date: **10/17/2022**

Line Paint Textured White - 6220

Print Date: 10/17/2022

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard
OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.