

Fortified Plexipave Ultra Dark Green - PLFDG ICP Construction Inc.

Version No: 4.4

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **08/14/2023** Print Date: **08/14/2023** S.GHS.USA.EN

SECTION 1 Identification

Product	Identifier

Product name	Fortified Plexipave Ultra Dark Green - PLFDG
Synonyms	Not Available
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	Sports Surface

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction Inc.
Address	150 Dascomb Road Andover, MA 01810 United States
Telephone	1-866-667-5119 1-978-623-9987
Fax	Not Available
Website	www.icpgroup.com
Email	sds@icpgroup.com

Emergency phone number

Association / Organis	tion ChemTel
Emergency telep	1-800-255-3924
Other emergency telep	one lers 1-813-248-0585

SECTION 2 Hazard(s) identification

Classification of the substance or mixture NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Carcinogenicity Category 1B, Specific Target Organ Toxicity - Repeated Exposure Category 2

Label elements

Hazard pictogram(s)



Signal word

Dange

Hazard statement(s)

H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Version No: **4.4** Page **2** of **9** Issue Date: **08/14/2023**

Fortified Plexipave Ultra Dark Green - PLFDG

Print Date: 08/14/2023

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves and protective clothing.
P202	Do not handle until all safety precautions have been read and understood.

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/ attention.
P314	Get medical advice/attention if you feel unwell.

Precautionary statement(s) Storage

P405 Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
107-21-1	1-5	ethylene glycol
14808-60-7*	30-60	silica crystalline - quartz
1333-86-4	0.1-1	carbon black

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: • Wash out immediately with water. • If irritation continues, seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Fire-fighting measures

Extinguishing media

- ► Foam.
- Dry chemical powder.

Version No: 4.4 Page 3 of 9 Issue Date: 08/14/2023

Fortified Plexipave Ultra Dark Green - PLFDG

Print Date: 08/14/2023

Special hazards arising from the substrate or mixture

Fire Incompatibility

▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Special protective equipment and precautions for fire-fighters

Fire Fighting

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Combustible.
- ▶ Slight fire hazard when exposed to heat or flame.

Combustion products include: Fire/Explosion Hazard

carbon dioxide (CO2)

other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Remove all ignition sources. Clean up all spills immediately.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs.
	► DO NOT allow clothing wet with material to stay in contact with skin

Other information

Store in original containers. ► Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

Suitable container

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

Storage incompatibility

► Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INCREDIENT DATA

INGREDIENT DATA						
Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	ethylene glycol	Ethylene glycol	Not Available	Not Available	Not Available	See Appendix D
US OSHA Permissible Exposure Limits (PELs) Table Z-1	silica crystalline - quartz	Quartz - respirable	0.05 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	silica crystalline - quartz	Silica: Crystalline: Quartz (Respirable)	10 (%SiO2+2) mg/m3 / 250 (%SiO2+5) mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	silica crystalline - quartz	Silica, crystalline (as respirable dust)	0.05 mg/m3	Not Available	Not Available	Ca; See Appendix A
US OSHA Permissible Exposure Limits (PELs) Table Z-1	carbon black	Carbon black	3.5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	carbon black	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available

Version No: 4.4 Page 4 of 9 Issue Date: 08/14/2023 Print Date: 08/14/2023

Fortified Plexipave Ultra Dark Green - PLFDG

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-3	carbon black	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	carbon black	Carbon black	3.5 mg/m3	Not Available	Not Available	Ca; TWA 0.1 mg PAHs/m3 [Carbon black in presence of polycyclic aromatic hydrocarbons (PAHs)] See Appendix A See

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
ethylene glycol	30 ppm	150 ppm	900 ppm
silica crystalline - quartz	0.075 mg/m3	33 mg/m3	200 mg/m3
carbon black	9 mg/m3	99 mg/m3	590 mg/m3

Ingredient	Original IDLH	Revised IDLH
ethylene glycol	Not Available	Not Available
silica crystalline - quartz	25 mg/m3 / 50 mg/m3	Not Available
carbon black	1,750 mg/m3	Not Available

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

Appendix C

Individual protection measures, such as personal protective equipment









Eye and face protection

- Safety glasses with side shields
- Chemical goggles.

Skin protection

See Hand protection below

Hands/feet protection

Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Body protection

See Other protection below

Other protection

- Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalentl
- Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges.

- Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels.
- Overalls.
- P.V.C apron.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available

Version No: **4.4** Page **5** of **9** Issue Date: **08/14/2023**

	Fortified Plexipave Ultra Dar	k Green - PLFDG		Print Date: 08/14/2023
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available	

pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	>130	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	91.67

SECTION 10 Stability and reactivity

Reactivity	See section 7
Reactivity	See Section /
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skir prior to the use of the material and ensure that any external damage is suitably protected.
Еуе	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems. There is ample evidence that this material can be regarded as being able to cause cancer in humans based on experiments and other information. Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.

TOXICITY	IRRITATION
Not Available	Not Available
TOXICITY	IRRITATION
dermal (mouse) LD50: >3500 mg/kg ^[1]	Eye (rabbit): 100 mg/1h - mild
Oral (Rat) LD50: >2000 mg/kg ^[2]	Eye (rabbit): 12 mg/m3/3D
	Eye (rabbit): 1440mg/6h-moderate
	Eye (rabbit): 500 mg/24h - mild
	Not Available TOXICITY dermal (mouse) LD50: >3500 mg/kg ^[1]

Version No: 4.4 Page 6 of 9 Issue Date: 08/14/2023

Fortified Plexipave Ultra Dark Green - PLFDG

Print Date: 08/14/2023

		Eye: no advers	se effect observed (not irritating) ^[1]
		Skin (rabbit): 5	555 mg(open)-mild
		Skin: no adver	se effect observed (not irritating) ^[1]
	TOXICITY	IRRITATION	
	Inhalation (Human)LCLo: 0.3 mg/m3/10Y ^[2]	Not Available	
silica crystalline - quartz	Inhalation (Human)TCLo: 16 mppcf*/8H/17.9Y ^[2]		
	Inhalation (Rat)TCLo: 50 mg/m3/6H/71W ^[2]		
	TOXICITY	IRRITATION	
carbon black	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye: no advers	se effect observed (not irritating) ^[1]
	Oral (Rat) LD50: >2000 mg/kg ^[1]	Skin: no adver	se effect observed (not irritating) ^[1]
			(-)
Legend:	Value obtained from Europe ECHA Registered Sull specified data extracted from RTECS - Register of To		tained from manufacturer's SDS. Unless otherwise
Legend:			tained from manufacturer's SDS. Unless otherwise
Legend:		oxic Effect of chemical Substances ted by Orica] Substance is reproducted by Orical S	tive effector in rats (birth defects). Mutagenic to rat ce
•	[Estimated Lethal Dose (human) 100 ml; RTECS quo For ethylene glycol: Ethylene glycol is quickly and extensively absorbed the	exic Effect of chemical Substances ated by Orica] Substance is reproduct throughout the gastrointestinal tract. I tently slow. stance has been classified by the IAF ARC) has classified occupational exp on what IARC considered sufficient	tive effector in rats (birth defects). Mutagenic to rat ce Limited information suggests that it is also absorbed RC as Group 1: CARCINOGENIC TO HUMANS osures to respirable (<5 um) crystalline silica as bein
ETHYLENE GLYCOL	[Estimated Lethal Dose (human) 100 ml; RTECS quo For ethylene glycol: Ethylene glycol is quickly and extensively absorbed the through the airways; absorption through skin is appar WARNING: For inhalation exposure ONLY: This subsorbed in the International Agency for Research on Cancer (IA carcinogenic to humans . This classification is based	nted by Orica] Substance is reproductive throughout the gastrointestinal tract. It is then the same of the same is the same is the same in the same is the same in the same is the same is the same in the same is	tive effector in rats (birth defects). Mutagenic to rat ce Limited information suggests that it is also absorbed RC as Group 1: CARCINOGENIC TO HUMANS osures to respirable (<5 um) crystalline silica as beine evidence from epidemiological studies of humans for ata identified in literature search.
ETHYLENE GLYCOL silica crystalline - quartz	[Estimated Lethal Dose (human) 100 ml; RTECS quo For ethylene glycol: Ethylene glycol is quickly and extensively absorbed the through the airways; absorption through skin is appar WARNING: For inhalation exposure ONLY: This subsorbed International Agency for Research on Cancer (IA carcinogenic to humans . This classification is based the carcinogenicity of inhaled silica in the forms of qualitation (rat) TCLo: 50 mg/m3/6h/90D-I Nil reported	nted by Orica] Substance is reproductive throughout the gastrointestinal tract. It is then the same of the same is the same is the same in the same is the same in the same is the same is the same in the same is	tive effector in rats (birth defects). Mutagenic to rat ce- Limited information suggests that it is also absorbed RC as Group 1: CARCINOGENIC TO HUMANS osures to respirable (<5 um) crystalline silica as being evidence from epidemiological studies of humans for ata identified in literature search.
ETHYLENE GLYCOL silica crystalline - quartz CARBON BLACK	[Estimated Lethal Dose (human) 100 ml; RTECS quo For ethylene glycol: Ethylene glycol is quickly and extensively absorbed the through the airways; absorption through skin is appar WARNING: For inhalation exposure QNLY: This substitute International Agency for Research on Cancer (IA carcinogenic to humans . This classification is based the carcinogenicity of inhaled silica in the forms of quickly linkly in the carcinogenicity of inhaled silica in the forms of quickly linkly inhalation (rat) TCLo: 50 mg/m3/6h/90D-I Nil reported WARNING: This substance has been classified by the	exic Effect of chemical Substances ated by Orica] Substance is reproduct throughout the gastrointestinal tract. I tently slow. stance has been classified by the IAF aRC) has classified occupational exp on what IARC considered sufficient artz and cristobalite. d No significant acute toxicological de e IARC as Group 2B: Possibly Carci	tive effector in rats (birth defects). Mutagenic to rat ce Limited information suggests that it is also absorbed RC as Group 1: CARCINOGENIC TO HUMANS osures to respirable (<5 um) crystalline silica as bein evidence from epidemiological studies of humans for ata identified in literature search.
ETHYLENE GLYCOL silica crystalline - quartz CARBON BLACK Acute Toxicity Skin Irritation/Corrosion	[Estimated Lethal Dose (human) 100 ml; RTECS quo For ethylene glycol: Ethylene glycol is quickly and extensively absorbed the through the airways; absorption through skin is appar WARNING: For inhalation exposure ONLY: This subsome The International Agency for Research on Cancer (IA carcinogenic to humans . This classification is based the carcinogenicity of inhaled silica in the forms of que Inhalation (rat) TCLo: 50 mg/m3/6h/90D-I Nil reported WARNING: This substance has been classified by the	notic Effect of chemical Substances of the day Orica] Substance is reproduct the day Orica] Substance is reproduct throughout the gastrointestinal tract. I tently slow. Stance has been classified by the IAFARC) has classified occupational expon what IARC considered sufficient artz and cristobalite. If No significant acute toxicological diese IARC as Group 2B: Possibly Carcinogenicity	tive effector in rats (birth defects). Mutagenic to rat ce Limited information suggests that it is also absorbed RC as Group 1: CARCINOGENIC TO HUMANS osures to respirable (<5 um) crystalline silica as beine evidence from epidemiological studies of humans for ata identified in literature search.
ETHYLENE GLYCOL silica crystalline - quartz CARBON BLACK Acute Toxicity	[Estimated Lethal Dose (human) 100 ml; RTECS quo For ethylene glycol: Ethylene glycol is quickly and extensively absorbed the through the airways; absorption through skin is appar WARNING: For inhalation exposure ONLY: This substitute International Agency for Research on Cancer (IA carcinogenic to humans . This classification is based the carcinogenicity of inhaled silica in the forms of que Inhalation (rat) TCLo: 50 mg/m3/6h/90D-I Nil reported WARNING: This substance has been classified by the	nted by Orica] Substance is reproductived by Orica] Substance is reproductive by Orica] Substance is reproductive by Orica] Substance is reproductive the gastrointestinal tract. It entity slow. It stance has been classified by the IAFARC) has classified occupational expon what IARC considered sufficient artz and cristobalite. If No significant acute toxicological dee IARC as Group 2B: Possibly Carcive Carcinogenicity Reproductivity	tive effector in rats (birth defects). Mutagenic to rat ce Limited information suggests that it is also absorbed RC as Group 1: CARCINOGENIC TO HUMANS osures to respirable (<5 um) crystalline silica as beine evidence from epidemiological studies of humans for ata identified in literature search.

Legend:

X − Data either not available or does not fill the criteria for classification
 ✓ − Data available to make classification

SECTION 12 Ecological information

Toxicity

	Endpoint	Test Duration (hr)	Species		Value	Source
Fortified Plexipave Ultra Dark Green - PLFDG	Not Available	Not Available	Not Available		Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Val	ue	Source
	EC50	96h	Algae or other aquatic plants	650	0-13000mg/l	1
ethylene glycol	EC50	48h	Crustacea	>10	00mg/l	2
	LC50	96h	Fish	805	0mg/l	4
	EC50(ECx)	Not Available	Algae or other aquatic plants	650	0-7500mg/l	1
	Endpoint	Test Duration (hr)	Species		Value	Source
silica crystalline - quartz	Not Available	Not Available	Not Available		Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value		Source
carbon black	EC50	72h	Algae or other aquatic plants	>0.2m	ıg/l	2
	EC50	48h	Crustacea	33.07	6-41.968mg/l	4
	LC50	96h	Fish	>100n	ng/l	2
	NOEC(ECx)	24h	Crustacea	3200n	ng/l	1
Legend:			CHA Registered Substances - Ecotoxicological Info			

DO NOT discharge into sewer or waterways.

Version No: **4.4** Page **7** of **9** Issue Date: **08/14/2023**

Fortified Plexipave Ultra Dark Green - PLFDG

Print Date: 08/14/2023

Ingredient	Persistence: Water/Soil	Persistence: Air	
ethylene glycol	LOW (Half-life = 24 days)	LOW (Half-life = 3.46 days)	

Bioaccumulative potential

Ingredient	Bioaccumulation	
ethylene glycol	LOW (BCF = 200)	

Mobility in soil

Ingredient	Mobility
ethylene glycol	HIGH (KOC = 1)

SECTION 13 Disposal considerations

Waste treatment methods

- ► Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Product / Packaging disposal

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.

SECTION 14 Transport information

Labels Required

Marine Pollutant NO

Shipping container and transport vehicle placarding and labeling may vary from the below information. Products that are regulated for transport will be packaged and marked as Dangerous Goods in Limited Quantities according to US DOT, IATA and IMDG regulations. In case of reshipment, it is the responsibility of the shipper to determine the appropriate labels and markings in accordance with applicable transport regulations.

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
ethylene glycol	Not Available
silica crystalline - quartz	Not Available
carbon black	Not Available

Transport in bulk in accordance with the IGC Code

Product name	Ship Type
ethylene glycol	Not Available
silica crystalline - quartz	Not Available
carbon black	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

ethylene glycol is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US - California Proposition 65 - Maximum Allowable Dose Levels (MADLs) for

Chemicals Causing Reproductive Toxicity

US - California Proposition 65 - Reproductive Toxicity

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65

US - Massachusetts - Right To Know Listed Chemicals

US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)

US Clean Air Act - Hazardous Air Pollutants

US DOE Temporary Emergency Exposure Limits (TEELs)

US EPA Integrated Risk Information System (IRIS)

US EPCRA Section 313 Chemical List

US NIOSH Recommended Exposure Limits (RELs)
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

silica crystalline - quartz is found on the following regulatory lists

Version No: 4.4 Page 8 of 9 Issue Date: 08/14/2023

Fortified Plexipave Ultra Dark Green - PLFDG

Print Date: 08/14/2023

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

carbon black is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

US - California Proposition 65 - Carcinogens

 $\ensuremath{\mathsf{US}}$ - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US National Toxicology Program (NTP) 15th Report Part A Known to be Human

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Carcinogens Listing

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Oction 317/312 nazara categories	
Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
n contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	Yes
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg	
ethylene glycol	5000	2270	

State Regulations

US. California Proposition 65



MARNING: This product can expose you to chemicals including silica crystalline - quartz, carbon black, which are known to the State of California to cause cancer, and ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (ethylene glycol; silica crystalline - quartz; carbon black)

Version No: **4.4** Page **9** of **9** Issue Date: **08/14/2023**

Fortified Plexipave Ultra Dark Green - PLFDG

Print Date: 08/14/2023

National Inventory	Status
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	08/14/2023
Initial Date	06/21/2022

CONTACT POINT

SDS Version Summary

Version	Date of Update	Sections Updated
3.4	08/14/2023	Disposal considerations - Disposal, Firefighting measures - Fire Fighter (extinguishing media), Firefighting measures - Fire Fighter (fire/explosion hazard), Firefighting measures - Fire Fighter (fire fighting), Handling and storage - Handling Procedure, Composition / information on ingredients - Ingredients, Accidental release measures - Spills (minor), Handling and storage - Storage (storage requirement), Handling and storage - Storage (suitable container)

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit₀

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorlTe, from Chemwatch.

^{**}PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES**