

# Plexichrome Ultra Performance Pacific Blue - PLPB ICP Construction Inc.

Version No: 6.8

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **08/16/2023** Print Date: **08/16/2023** S.GHS.USA.EN

# **SECTION 1 Identification**

| Drac | 14 | 144 | ntifier |
|------|----|-----|---------|
|      |    |     |         |

| Product name                  | Plexichrome Ultra Performance Pacific Blue - PLPB |  |
|-------------------------------|---|--|
| Synonyms                      | Not Available                                     |  |
| Other means of identification | Not Available                                     |  |

#### Recommended use of the chemical and restrictions on use

| Polovant identified uses | Sporte Surface |
|--------------------------|----------------|
| Relevant identified uses | Sports Surrace |

# Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

| Registered company name | ICP Construction Inc.                            |
|-------------------------|--|
| Address                 | 150 Dascomb Road Andover, MA 01810 United States |
| Telephone               | 1-866-667-5119 1-978-623-9987                    |
| Fax                     | Not Available                                    |
| Website                 | www.icpgroup.com                                 |
| Email                   | sds@icpgroup.com                                 |

# Emergency phone number

| Association / Organis | tion ChemTel            |
|-----------------------|-------------------------|
| Emergency telep       | 1-800-255-3924          |
| Other emergency telep | one lers 1-813-248-0585 |

# SECTION 2 Hazard(s) identification

# Classification of the substance or mixture NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Carcinogenicity Category 1B, Specific Target Organ Toxicity - Repeated Exposure Category 1

# Label elements

Hazard pictogram(s)



Signal word

Dange

# Hazard statement(s)

| H350 | May cause cancer.   |
|------|---|
| H372 | Causes damage to organs through prolonged or repeated exposure. |

 Version No: 6.8
 Page 2 of 9
 Issue Date: 08/16/2023

# Plexichrome Ultra Performance Pacific Blue - PLPB

Print Date: 08/16/2023

#### Hazard(s) not otherwise classified

Not Applicable

#### Precautionary statement(s) General

| P101 | If medical advice is needed, have product container or label at hand. |
|------|---|
| P102 | Keep out of reach of children.  |
| P103 | Read label before use.  |

# Precautionary statement(s) Prevention

| P201 | Obtain special instructions before use.                                   |  |
|------|---|--|
| P260 | Do not breathe mist/vapours/spray.  |  |
| P280 | Wear protective gloves and protective clothing.                           |  |
| P270 | Do not eat, drink or smoke when using this product.                       |  |
| P202 | Do not handle until all safety precautions have been read and understood. |  |
| P264 | Wash all exposed external body areas thoroughly after handling.           |  |
|      |   |  |

#### Precautionary statement(s) Response

| P308+P313 | IF exposed or concerned: Get medical advice/ attention. |
|-----------|---|
| P314      | Get medical advice/attention if you feel unwell.        |

#### Precautionary statement(s) Storage

|  | P405 | Store locked up. |
|--|------|------------------|
|--|------|------------------|

#### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

#### **SECTION 3 Composition / information on ingredients**

#### Substances

See section below for composition of Mixtures

#### **Mixtures**

| CAS No      | %[weight] | Name                        |
|-------------|-----------|-----------------------------|
| 107-21-1    | 0.1-1     | ethylene glycol             |
| 14808-60-7* | 10-30     | silica crystalline - quartz |

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

# **SECTION 4 First-aid measures**

# Description of first aid measures

| Eye Contact  | If this product comes in contact with eyes:  • Wash out immediately with water.  • If irritation continues, seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
|--------------|--|
| Skin Contact | If skin contact occurs:  Immediately remove all contaminated clothing, including footwear.  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.                          |
| Inhalation   | <ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>  |
| Ingestion    | <ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>  |

# Most important symptoms and effects, both acute and delayed

See Section 11

# Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5 Fire-fighting measures**

# **Extinguishing media**

- ▶ Foam
- ► Dry chemical powder.

Version No: 6.8 Page 3 of 9 Issue Date: 08/16/2023

#### Plexichrome Ultra Performance Pacific Blue - PLPB

Print Date: 08/16/2023

#### Special hazards arising from the substrate or mixture

Fire Incompatibility

▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

#### Special protective equipment and precautions for fire-fighters

#### Fire Fighting

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Combustible.
- ▶ Slight fire hazard when exposed to heat or flame.

Combustion products include: Fire/Explosion Hazard

carbon dioxide (CO2)

other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

#### **SECTION 6 Accidental release measures**

# Personal precautions, protective equipment and emergency procedures

See section 8

# **Environmental precautions**

See section 12

#### Methods and material for containment and cleaning up

| Minor Spills | Remove all ignition sources.     Clean up all spills immediately.   |
|--------------|---|
| Major Spills | <ul> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> </ul> |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

#### Precautions for safe handling

| Safe handling     | Avoid all personal contact, including inhalation.     Wear protective clothing when risk of exposure occurs.     DO NOT allow clothing wet with material to stay in contact with skin |
|-------------------|---|
| Other information | <ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> </ul>   |

# Conditions for safe storage, including any incompatibilities

| Suitable container      | <ul> <li>Metal can or drum</li> <li>Packaging as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul> |
|-------------------------|--|
| Storage incompatibility | Avoid reaction with oxidising agents   |

# **SECTION 8 Exposure controls / personal protection**

# **Control parameters**

# Occupational Exposure Limits (OEL)

#### INGREDIENT DATA

| Source  | Ingredient                     | Material name                            | TWA   | STEL             | Peak             | Notes                 |  |
|---|--------------------------------|--|---|------------------|------------------|-----------------------|--|
| US NIOSH Recommended<br>Exposure Limits (RELs)          | ethylene glycol                | Ethylene glycol                          | Not Available                               | Not<br>Available | Not<br>Available | See Appendix D        |  |
| US OSHA Permissible Exposure<br>Limits (PELs) Table Z-1 | silica crystalline -<br>quartz | Quartz - respirable                      | 0.05 mg/m3                                  | Not<br>Available | Not<br>Available | Not Available         |  |
| US OSHA Permissible Exposure<br>Limits (PELs) Table Z-3 | silica crystalline -<br>quartz | Silica: Crystalline: Quartz (Respirable) | 10 (%SiO2+2) mg/m3 / 250<br>(%SiO2+5) mppcf | Not<br>Available | Not<br>Available | Not Available         |  |
| US NIOSH Recommended<br>Exposure Limits (RELs)          | silica crystalline -<br>quartz | Silica, crystalline (as respirable dust) | 0.05 mg/m3                                  | Not<br>Available | Not<br>Available | Ca; See<br>Appendix A |  |

# Emergency Limits

| Ingredient                  | TEEL-1      | TEEL-2   | TEEL-3    |
|-----------------------------|-------------|----------|-----------|
| ethylene glycol             | 30 ppm      | 150 ppm  | 900 ppm   |
| silica crystalline - quartz | 0.075 mg/m3 | 33 mg/m3 | 200 mg/m3 |

Issue Date: 08/16/2023 Version No: 6.8 Page 4 of 9 Print Date: 08/16/2023

#### Plexichrome Ultra Performance Pacific Blue - PLPB

| Ingredient                  | Original IDLH       | Revised IDLH  |
|-----------------------------|---------------------|---------------|
| ethylene glycol             | Not Available       | Not Available |
| silica crystalline - quartz | 25 mg/m3 / 50 mg/m3 | Not Available |

#### **Exposure controls**

# Appropriate engineering Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can controls be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. Individual protection measures, such as personal protective equipment Safety glasses with side shields. Eye and face protection Chemical goggles. Skin protection See Hand protection below

#### Hands/feet protection

▶ Wear chemical protective gloves, e.g. PVC.

#### Wear safety footwear or safety gumboots, e.g. Rubber

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### **Body protection**

See Other protection below

- Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalentl
- Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges.

#### Other protection

- Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels.
- Overalls.
- P.V.C apron.

# Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

# **SECTION 9 Physical and chemical properties**

#### Information on basic physical and chemical properties Not Available **Appearance** Physical state Relative density (Water = 1) Not Available Liquid Partition coefficient n-octanol Odour Not Available Not Available / water Odour threshold Not Available Auto-ignition temperature (°C) Not Available Decomposition Not Available Not Available pH (as supplied) temperature (°C) Melting point / freezing point Not Available Not Available Viscosity (cSt) (°C) Initial boiling point and boiling Not Available Molecular weight (g/mol) Not Available range (°C) Not Available Flash point (°C) >130 Taste **Evaporation rate** Not Available **Explosive properties** Not Available Flammability Not Applicable Oxidising properties Not Available Surface Tension (dyn/cm or Upper Explosive Limit (%) Not Available Not Available mN/m) Lower Explosive Limit (%) Not Available Volatile Component (%vol) Not Available Vapour pressure (kPa) Not Available Gas group Not Available

Version No: 6.8 Page 5 of 9 Issue Date: 08/16/2023 Print Date: 08/16/2023

# Plexichrome Ultra Performance Pacific Blue - PLPB

| Solubility in water | Immiscible | pH as a solution (1%) | Not Available |
|---------------------|------------|-----------------------|---------------|

VOC g/L

79

# **SECTION 10 Stability and reactivity**

Vapour density (Air = 1)

Not Available

| Reactivity                         | See section 7   |
|------------------------------------|---|
| Chemical stability                 | Unstable in the presence of incompatible materials. Product is considered stable. |
| Possibility of hazardous reactions | See section 7   |
| Conditions to avoid                | See section 7   |
| Incompatible materials             | See section 7   |
| Hazardous decomposition products   | See section 5   |

# **SECTION 11 Toxicological information**

|             | _         |         |         |
|-------------|-----------|---------|---------|
| Information | on toxico | Indical | effects |

| Inhaled      | The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.  |
|--------------|--|
| Ingestion    | The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.   |
| Skin Contact | Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.  There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the ski prior to the use of the material and ensure that any external damage is suitably protected. |
| Еуе          | Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).   |
| Chronic      | Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems.  There is ample evidence that this material can be regarded as being able to cause cancer in humans based on experiments and other information.  Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.  This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.   |

| Plexichrome Ultra                 | TOXICITY  | IRRITATION  |
|-----------------------------------|---|---|
| erformance Pacific Blue -<br>PLPB | Not Available   | Not Available   |
|                                   | TOXICITY  | IRRITATION  |
|                                   | dermal (mouse) LD50: >3500 mg/kg <sup>[1]</sup>           | Eye (rabbit): 100 mg/1h - mild  |
|                                   | Oral (Rat) LD50: >2000 mg/kg <sup>[2]</sup>               | Eye (rabbit): 12 mg/m3/3D   |
| athulana mhuaal                   |   | Eye (rabbit): 1440mg/6h-moderate  |
| ethylene glycol                   |   | Eye (rabbit): 500 mg/24h - mild   |
|                                   |   | Eye: no adverse effect observed (not irritating) <sup>[1]</sup>             |
|                                   |   | Skin (rabbit): 555 mg(open)-mild  |
|                                   |   | Skin: no adverse effect observed (not irritating) <sup>[1]</sup>            |
|                                   | TOXICITY  | IRRITATION  |
|                                   | Inhalation (Human)LCLo: 0.3 mg/m3/10Y <sup>[2]</sup>      | Not Available   |
| silica crystalline - quartz       | Inhalation (Human)TCLo: 16 mppcf*/8H/17.9Y <sup>[2]</sup> |   |
|                                   | Inhalation (Rat)TCLo: 50 mg/m3/6H/71W <sup>[2]</sup>      |   |
| Legend:                           | 1 Value obtained from Europe ECHA Registered Substances   | - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwis |

specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

ETHYLENE GLYCOL

[Estimated Lethal Dose (human) 100 ml; RTECS quoted by Orica] Substance is reproductive effector in rats (birth defects). Mutagenic to rat cells. For ethylene glycol:

Ethylene glycol is quickly and extensively absorbed throughout the gastrointestinal tract. Limited information suggests that it is also absorbed through the airways; absorption through skin is apparently slow.

 Version No: 6.8
 Page 6 of 9
 Issue Date: 08/16/2023

#### Plexichrome Ultra Performance Pacific Blue - PLPB

Print Date: 08/16/2023

silica crystalline - quartz

WARNING: For inhalation exposure ONLY: This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS

ne - quartz
The International Agency for Research on Cancer (IARC) has classified occupational exposures to respirable (<5 um) crystalline silica as being carcinogenic to humans. This classification is based on what IARC considered sufficient evidence from epidemiological studies of humans for the carcinogenicity of inhaled silica in the forms of quartz and cristobalite.

Acute Toxicity X Carcinogenicity V

Skin Irritation/Corrosion X Reproductivity X

Serious Eye Damage/Irritation X STOT - Single Exposure X

Respiratory or Skin sensitisation

Legend:

**Aspiration Hazard** 

★ - Data either not available or does not fill the criteria for classification

Data available to make classification

# **SECTION 12 Ecological information**

Mutagenicity

#### Toxicity

| Plexichrome Ultra               | Endpoint         | Test Duration (hr) | Species   | Value         | Source                |
|---------------------------------|------------------|--------------------|---|---------------|-----------------------|
| Performance Pacific Blue - PLPB | Not<br>Available | Not Available      | Not Available   | Not<br>Availa | Not<br>able Available |
|                                 | Endpoint         | Test Duration (hr) | Species   | Value         | Source                |
|                                 | EC50             | 96h                | Algae or other aquatic plants   | 6500-13000    | Omg/I 1               |
| ethylene glycol                 | EC50             | 48h                | Crustacea   | >100mg/l      | 2                     |
|                                 | LC50             | 96h                | Fish  | 8050mg/l      | 4                     |
|                                 | EC50(ECx)        | Not Available      | Algae or other aquatic plants   | 6500-7500r    | ng/l 1                |
|                                 | Endpoint         | Test Duration (hr) | Species   | Value         | Source                |
| silica crystalline - quartz     | Not<br>Available | Not Available      | Not Available   | Not<br>Availa | Not<br>able Available |
| Legend:                         | Ecotox databa    |                    | Registered Substances - Ecotoxicological Info<br>tic Hazard Assessment Data 6. NITE (Japan, | •             | •                     |

#### DO NOT discharge into sewer or waterways.

#### Persistence and degradability

| Ingredient      | Persistence: Water/Soil   | Persistence: Air            |
|-----------------|---------------------------|-----------------------------|
| ethylene glycol | LOW (Half-life = 24 days) | LOW (Half-life = 3.46 days) |

# Bioaccumulative potential

| Ingredient      | Bioaccumulation |
|-----------------|-----------------|
| ethylene glycol | LOW (BCF = 200) |

# Mobility in soil

| Ingredient      | Mobility       |
|-----------------|----------------|
| ethylene glycol | HIGH (KOC = 1) |

# **SECTION 13 Disposal considerations**

#### Waste treatment methods

- ► Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area

#### Product / Packaging disposal

# DO NOT allow wash water from cleaning or process equipment to enter drains.

- It may be necessary to collect all wash water for treatment before disposal.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.

# **SECTION 14 Transport information**

# Labels Required

| Marine Pollutant | NO  |
|------------------|-----|
| Marine Pollutant | INU |

Shipping container and transport vehicle placarding and labeling may vary from the below information. Products that are regulated for transport will be packaged and marked as

Version No: **6.8** Page **7** of **9** 

#### Plexichrome Ultra Performance Pacific Blue - PLPB

Issue Date: **08/16/2023**Print Date: **08/16/2023** 

Dangerous Goods in Limited Quantities according to US DOT, IATA and IMDG regulations. In case of reshipment, it is the responsibility of the shipper to determine the appropriate labels and markings in accordance with applicable transport regulations.

#### Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

# Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name                | Group         |
|-----------------------------|---------------|
| ethylene glycol             | Not Available |
| silica crystalline - quartz | Not Available |

#### Transport in bulk in accordance with the IGC Code

| Product name                | Ship Type     |
|-----------------------------|---------------|
| ethylene glycol             | Not Available |
| silica crystalline - quartz | Not Available |

#### **SECTION 15 Regulatory information**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

Chemical Footprint Project - Chemicals of High Concern List

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US - California Proposition 65 - Maximum Allowable Dose Levels (MADLs) for

Chemicals Causing Reproductive Toxicity

US - California Proposition 65 - Reproductive Toxicity

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65

List
US - Massachusetts - Right To Know Listed Chemicals

US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)

US Clean Air Act - Hazardous Air Pollutants

US DOE Temporary Emergency Exposure Limits (TEELs)

US EPA Integrated Risk Information System (IRIS)

US EPCRA Section 313 Chemical List

US NIOSH Recommended Exposure Limits (RELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### silica crystalline - quartz is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

US National Toxicology Program (NTP) 15th Report Part A Known to be Human Carcinogens

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Carcinogens Listing

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### **Federal Regulations**

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

# Section 311/312 hazard categories

| Flammable (Gases, Aerosols, Liquids, or Solids) | No  |
|---|-----|
| Gas under pressure                              | No  |
| Explosive                                       | No  |
| Self-heating                                    | No  |
| Pyrophoric (Liquid or Solid)                    | No  |
| Pyrophoric Gas                                  | No  |
| Corrosive to metal                              | No  |
| Oxidizer (Liquid, Solid or Gas)                 | No  |
| Organic Peroxide                                | No  |
| Self-reactive                                   | No  |
| In contact with water emits flammable gas       | No  |
| Combustible Dust                                | No  |
| Carcinogenicity                                 | Yes |
| Acute toxicity (any route of exposure)          | No  |
| Reproductive toxicity                           | No  |
| Skin Corrosion or Irritation                    | No  |
| Respiratory or Skin Sensitization               | No  |
| Serious eye damage or eye irritation            |     |

Version No: 6.8 Page 8 of 9 Issue Date: 08/16/2023 Print Date: 08/16/2023

#### Plexichrome Ultra Performance Pacific Blue - PLPB

Yes Specific target organ toxicity (single or repeated exposure) Aspiration Hazard No Germ cell mutagenicity No

#### US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

| Name            | Reportable Quantity in Pounds (lb) | Reportable Quantity in kg |
|-----------------|------------------------------------|---------------------------|
| ethylene glycol | 5000                               | 2270                      |

# State Regulations

Simple Asphyxiant

#### US. California Proposition 65

Hazards Not Otherwise Classified



MARNING: This product can expose you to chemicals including silica crystalline - quartz, which is known to the State of California to cause cancer, and ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

#### National Inventory Status

| National Inventory                                 | Status   |  |
|--|--|--|
| Australia - AIIC / Australia<br>Non-Industrial Use | Yes  |  |
| Canada - DSL                                       | Yes  |  |
| Canada - NDSL                                      | No (ethylene glycol; silica crystalline - quartz)  |  |
| China - IECSC                                      | Yes  |  |
| Europe - EINEC / ELINCS / NLP                      | Yes  |  |
| Japan - ENCS                                       | Yes  |  |
| Korea - KECI                                       | Yes  |  |
| New Zealand - NZIoC                                | Yes  |  |
| Philippines - PICCS                                | Yes  |  |
| USA - TSCA   | Yes  |  |
| Taiwan - TCSI                                      | Yes  |  |
| Mexico - INSQ                                      | Yes  |  |
| Vietnam - NCI                                      | Yes  |  |
| Russia - FBEPH                                     | Yes  |  |
| Legend:  | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |  |

# **SECTION 16 Other information**

| Revision Date | 08/16/2023 |
|---------------|------------|
| Initial Date  | 03/04/2021 |

#### CONTACT POINT

\*\*PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES\*\*

# **SDS Version Summary**

| Version | Date of Update | Sections Updated                                       |
|---------|----------------|--|
| 5.8     | 08/16/2023     | Composition / information on ingredients - Ingredients |

# Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

# **Definitions and abbreviations**

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

Continued...

No

No

Version No: 6.8 Page 9 of 9 Issue Date: 08/16/2023

# Plexichrome Ultra Performance Pacific Blue - PLPB

Print Date: 08/16/2023

DSL: Domestic Substances List NDSL: Non-Domestic Substances List

EICSC: Inventory of Existing Chemical Substance in China
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.