

Premier Sports Coatings US Blue - 2534 ICP Construction Inc.

Version No: 3.3

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **08/02/2023** Print Date: **08/02/2023** S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	Premier Sports Coatings US Blue - 2534	
Synonyms	2534	
Other means of identification	Not Available	

Recommended use of the chemical and restrictions on use

Relevant identified uses	Sports Surfaces

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction Inc.	
Address	50 Dascomb Road Andover, MA 01810 United States	
Telephone	366-667-5119 1-978-623-9987	
Fax	Not Available	
Website	www.icpgroup.com	
Email	sds@icpgroup.com	

Emergency phone number

Association / Organis	tion ChemTel
Emergency telep	1-800-255-3924
Other emergency telep	one lers 1-813-248-0585

SECTION 2 Hazard(s) identification

Classification of the substance or mixture NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification C

Carcinogenicity Category 2, Specific Target Organ Toxicity - Repeated Exposure Category 2

Label elements

Hazard pictogram(s)



Signal word

Warning

Hazard statement(s)

H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Version No: **3.3** Page **2** of **11** Issue Date: **08/02/2023**

Premier Sports Coatings US Blue - 2534

Print Date: 08/02/2023

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read label before use.	

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.	
P260	Do not breathe mist/vapours/spray.	
P280	Wear protective gloves and protective clothing.	
P202	Do not handle until all safety precautions have been read and understood.	

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/ attention.	
P314	P314 Get medical advice/attention if you feel unwell.	

Precautionary statement(s) Storage

P405 Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
107-21-1	1-5	ethylene glycol
1333-86-4	0.1-1	carbon black
13463-67-7*	1-5	Titanium Dioxide Ti02
14808-60-7	5-10	silica crystalline - quartz
25265-77-4	1-5	2.2.4-trimethyl-1,3-pentanediol monoisobutyrate

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: • Wash out immediately with water. • If irritation continues, seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.	
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.	
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary. 	
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. 	

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Fire-fighting measures

Extinguishing media

► Foam.

Version No: 3.3 Page 3 of 11 Issue Date: 08/02/2023 Print Date: 08/02/2023

Premier Sports Coatings US Blue - 2534

Dry chemical powder.

Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Special protective equipment and precautions for fire-fighters

Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Combustible.
- Slight fire hazard when exposed to heat or flame.

Combustion products include: carbon dioxide (CO2)

Fire/Explosion Hazard

other pyrolysis products typical of burning organic material.

May emit poisonous fumes

May emit corrosive fumes.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Remove all ignition sources. Clean up all spills immediately.	
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. 	

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe	handling

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs. ▶ DO NOT allow clothing wet with material to stay in contact with skin
- Other information
- ▶ Store in original containers.
- Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

Suitable container

Storage incompatibility

- ▶ Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

Silicas

- react with hydrofluoric acid to produce silicon tetrafluoride gas
- react with xenon hexafluoride to produce explosive xenon trioxide
- reacts exothermically with oxygen difluoride, and explosively with chlorine trifluoride (these halogenated materials are not commonplace industrial materials) and other fluorine-containing compounds
- may react with fluorine, chlorates
- are incompatible with strong oxidisers, manganese trioxide, chlorine trioxide, strong alkalis, metal oxides, concentrated orthophosphoric acid, vinyl acetate
- may react vigorously when heated with alkali carbonates.
- ▶ Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	ethylene glycol	Ethylene glycol	Not Available	Not Available	Not Available	See Appendix D
US OSHA Permissible Exposure Limits (PELs) Table Z-1	carbon black	Carbon black	3.5 mg/m3	Not Available	Not Available	Not Available

Version No: 3.3 Page 4 of 11 Issue Date: 08/02/2023 Print Date: 08/02/2023

Premier Sports Coatings US Blue - 2534

Source	Ingredient	Material name	TW	/A	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-3	carbon black	Inert or Nuisance Dust: Total Dust		mg/m3 / 50 pcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	carbon black	Inert or Nuisance Dust: Respirable fraction	5 n	ng/m3 / 15 mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	carbon black	Carbon black	3.5	i mg/m3	Not Available	Not Available	Ca; TWA 0.1 mg PAHs/m3 [Carbon black in presence of polycyclic aromatic hydrocarbons (PAHs)] See Appendix A See Appendix C
US OSHA Permissible Exposure Limits (PELs) Table Z-1	Titanium Dioxide Ti02	Titanium dioxide - Total dust	15	15 mg/m3		Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Titanium Dioxide Ti02	Inert or Nuisance Dust: Total Dust		mg/m3 / 50 opcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Titanium Dioxide Ti02	Inert or Nuisance Dust: Respirable fraction	5 n	ng/m3 / 15 mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	Titanium Dioxide Ti02	Titanium dioxide	No	t Available	Not Available	Not Available	Ca; See Appendix A
US OSHA Permissible Exposure Limits (PELs) Table Z-1	silica crystalline - quartz	Quartz - respirable	0.0	95 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	silica crystalline - quartz	Silica: Crystalline: Quartz (Respirable)	mg	(%SiO2+2) y/m3 / 250 SiO2+5) mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	silica crystalline - quartz	Silica, crystalline (as respirable dust)	0.0	95 mg/m3	Not Available	Not Available	Ca; See Appendix A
Emergency Limits							
Ingredient	TEEL-1			TEEL-2			TEEL-3
ethylene glycol	30 ppm			150 ppm			900 ppm
carbon black	9 mg/m3		99 mg/m3			590 mg/m3	
Titanium Dioxide Ti02	30 mg/m3	0 mg/m3 330 mg/m3				2,000 mg/m3	
silica crystalline - quartz	0.075 mg/m3		33 mg/m3			200 mg/m3	
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	13 mg/m3	140 mg/m3			840 mg/m3		
Ingredient	Original IDLH					Revised	IDLH
ethylene glycol	Not Available					Not Avai	lable
carbon black	1,750 mg/m3				lable		
Titanium Dioxide Ti02	5,000 mg/m3					Not Avai	lable
silica crystalline - quartz	25 mg/m3 / 50 m	ng/m3				Not Avai	lable
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Not Available					Not Avai	lable
Exposure controls							
Appropriate engineering controls							hazard. Well-designed engineering controls can o provide this high level of protection.
Individual protection measures, such as personal protective equipment							
Eye and face protection		Safety glasses with side shields.Chemical goggles.					
Skin protection	See Hand protect	ction below					
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. 						
Body protection	See Other prote	ction below					
Other protection	Employees (smocks, co national equ	Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent] Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges.					

Version No: **3.3** Page **5** of **11** Issue Date: **08/02/2023**

Premier Sports Coatings US Blue - 2534

Print Date: 08/02/2023

- Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels.
- Overalls
- P.V.C apron.

Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

If inhalation risk above the TLV exists, wear approved dust respirator.

Use respirators with protection factors appropriate for the exposure level.

- ▶ Up to 5 X TLV, use valveless mask type; up to 10 X TLV, use 1/2 mask dust respirator
- ▶ Up to 50 X TLV, use full face dust respirator or demand type C air supplied respirator
- ▶ Up to 500 X TLV, use powered air-purifying dust respirator or a Type C pressure demand supplied-air respirator
- Over 500 X TLV wear full-face self-contained breathing apparatus with positive pressure mode or a combination respirator with a Type C positive pressure supplied-air full-face respirator and an auxiliary self-contained breathing apparatus operated in pressure demand or other positive pressure mode
- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical	and chemical properties		
Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	>130	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	130

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Version No: 3.3 Page 6 of 11 Issue Date: 08/02/2023 Print Date: 08/02/2023

Premier Sports Coatings US Blue - 2534

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.			
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.			
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.			
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directoracterised by tearing or conjunctival redness (as with windburn).	rectives), direct contact with the eye may produce transient discomfort		
Chronic	Repeated or long-term occupational exposure is likely to produce cumula Strong evidence exists that this substance may cause irreversible mutati There is sufficient evidence to suggest that this material directly causes of Crystalline silicas activate the inflammatory response of white blood cells silicas reduces lung capacity and predisposes to chest infections.	ons (though not lethal) even following a single exposure. cancer in humans.		
Premier Sports Coatings US Blue - 2534	TOXICITY Not Available	IRRITATION Not Available		
Diuc 2007	Not Available	Not Available		
	TOXICITY	IRRITATION		
	dermal (mouse) LD50: >3500 mg/kg ^[1]	Eye (rabbit): 100 mg/1h - mild		
	Oral (Rat) LD50: >2000 mg/kg ^[2]	Eye (rabbit): 12 mg/m3/3D		
attatan atau		Eye (rabbit): 1440mg/6h-moderate		
ethylene glycol		Eye (rabbit): 500 mg/24h - mild		
		Eye: no adverse effect observed (not irritating) ^[1]		
		Skin (rabbit): 555 mg(open)-mild		
		Skin: no adverse effect observed (not irritating) ^[1]		
	TOWNER	IDDITATION		
	TOXICITY Description Descri	IRRITATION		
carbon black	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]		
	Oral (Rat) LD50: >2000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]		
	TOXICITY	IRRITATION		
	dermal (hamster) LD50: >=10000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]		
Titanium Dioxide Ti02	Inhalation(Rat) LC50: >2.28 mg/l4h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]		
	Oral (Rat) LD50: >=2000 mg/kg ^[1]			
silica crystalline - quartz	TOXICITY	IRRITATION		
	Oral (Rat) LD50: 500 mg/kg ^[2]	Not Available		
	TOXICITY	IRRITATION		
	dermal (guinea pig) LD50: >19 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]		
2,2,4-trimethyl-1,3-pentanediol	Oral (Rat) LD50: >3200 mg/kg ^[2]	Eyes - Moderate irritant *		
monoisobutyrate		Skin - Slight irritant *		
		Skin (rabbit): mild ***		
		Skin: no adverse effect observed (not irritating) ^[1]		
Legend:	Nalue obtained from Europe ECHA Registered Substances - Acute to. specified data extracted from RTECS - Register of Toxic Effect of chemical contents.	· ·		
Premier Sports Coatings US Blue - 2534	Laboratory (in vitro) and animal studies show, exposure to the material n producing mutation.	nay result in a possible risk of irreversible effects, with the possibility of		
ETHYLENE GLYCOL	producing mutation. [Estimated Lethal Dose (human) 100 ml; RTECS quoted by Orica] Substance is reproductive effector in rats (birth defects). Mutagenic to rat cells. For ethylene glycol: Ethylene glycol is quickly and extensively absorbed throughout the gastrointestinal tract. Limited information suggests that it is also absorbed through the airways; absorption through skin is apparently slow.			
CARRON RI ACK	Inhalation (rat) TCLo: 50 mg/m3/6h/90D-l Nil reported No significant acu	te toxicological data identified in literature search.		
CARBON BLACK	WARNING: This substance has been classified by the IARC as Group 2	B: Possibly Carcinogenic to Humans.		
SILICA CRYSTALLINE - QUARTZ	WARNING: For inhalation exposure ONLY: This substance has been cla The International Agency for Research on Cancer (IARC) has classified			

Version No: 3.3 Page **7** of **11** Issue Date: 08/02/2023

Premier Sports Coatings US Blue - 2534

Print Date: 08/02/2023

2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE carcinogenic to humans . This classification is based on what IARC considered sufficient evidence from epidemiological studies of humans for the carcinogenicity of inhaled silica in the forms of quartz and cristobalite.

Not a skin sensitiser (guinea pig, Magnusson-Kligman) *** Ames Test: negative *** Micronucleus, mouse: negative *** Not mutagenic *** No effects on fertility or foetal development seen in the rat *** * [SWIFT] ** [Eastman] *** [Perstop]

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Acute Toxicity	×	Carcinogenicity	✓
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	•
Mutagenicity	×	Aspiration Hazard	×

Legend:

🗶 – Data either not available or does not fill the criteria for classification

— Data available to make classification

SECTION 12 Ecological information

Toxicity

Premier Sports Coatings US	Endpoint	Test Duration (hr)	Species		Value	Source
Blue - 2534	Not Available	Not Available	Not Available		Not Available	Not Availabl
	Endpoint	Test Duration (hr)	Species	Va	ilue	Sourc
	EC50	96h	Algae or other aquatic plants	65	i00-13000mg/l	1
ethylene glycol	EC50	48h	Crustacea	>1	00mg/l	2
	LC50	96h	Fish	Fish 8050mg/		4
	EC50(ECx)	Not Available	Algae or other aquatic plants	65	600-7500mg/l	1
	Endpoint	Test Duration (hr)	Species	Valu	e	Source
	EC50	72h	Algae or other aquatic plants	>0.2	mg/l	2
carbon black	EC50	48h	Crustacea	33.0	76-41.968mg/l	4
	LC50	96h	Fish	>100	mg/l	2
	NOEC(ECx)	24h	Crustacea	3200	lmg/l	1
	Endpoint	Test Duration (hr)	Species		Value	Source
	BCF	1008h	Fish		<1.1-9.6	7
	EC50	72h	Algae or other aquatic plants	Algae or other aquatic plants 3.7		4
Titanium Dioxide Ti02	EC50	48h	Crustacea	Crustacea		2
	EC50	96h	Algae or other aquatic plants	Algae or other aquatic plants		2
	LC50	96h	Fish	Fish 1.85		4
	NOEC(ECx)	672h	Fish		>=0.004mg/L	2
	Endpoint	Test Duration (hr)	Species		Value	Source
silica crystalline - quartz	Not Available	Not Available	Not Available		Not Available	Not Availab
	Endpoint	Test Duration (hr)	Species		Value	Source
	EC50	72h	Algae or other aquatic plants		15mg/l	Not Availab
2,4-trimethyl-1,3-pentanediol monoisobutyrate	EC50	48h	Crustacea	Crustacea >		2
monoisobutyrate	NOEC(ECx)	72h	Algae or other aquatic plants	Algae or other aquatic plants 3.2		1
	LC50	96h	Fish		16mg/l	Not Availab

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethylene glycol	LOW (Half-life = 24 days)	LOW (Half-life = 3.46 days)
Titanium Dioxide Ti02	HIGH	HIGH

Version No: 3.3 Page **8** of **11** Issue Date: 08/02/2023 Print Date: 08/02/2023

Premier Sports Coatings US Blue - 2534

Ingredient	Persistence: Water/Soil	Persistence: Air
2,2,4-trimethyl-1,3-pentanediol	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
ethylene glycol	LOW (BCF = 200)
Titanium Dioxide Ti02	LOW (BCF = 10)
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	LOW (LogKOW = 2.9966)

Mobility in soil

Ingredient	Mobility
ethylene glycol	HIGH (KOC = 1)
Titanium Dioxide Ti02	LOW (KOC = 23.74)
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	LOW (KOC = 22.28)

SECTION 13 Disposal considerations

Waste treatment methods

- ▶ Containers may still present a chemical hazard/ danger when empty. ▶ Return to supplier for reuse/ recycling if possible.
- Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their

Product / Packaging disposal

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- ▶ Consult State Land Waste Authority for disposal.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
Wallie Foliutant	INO

Shipping container and transport vehicle placarding and labeling may vary from the below information. Products that are regulated for transport will be packaged and marked as Dangerous Goods in Limited Quantities according to US DOT, IATA and IMDG regulations. In case of reshipment, it is the responsibility of the shipper to determine the appropriate labels and markings in accordance with applicable transport regulations

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
ethylene glycol	Not Available
carbon black	Not Available
Titanium Dioxide Ti02	Not Available
silica crystalline - quartz	Not Available
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Not Available

Transport in bulk in accordance with the IGC Code

Product name	Ship Type
ethylene glycol	Not Available
carbon black	Not Available
Titanium Dioxide Ti02	Not Available
silica crystalline - quartz	Not Available
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Not Available

SECTION 15 Regulatory information

Version No: **3.3** Page **9** of **11** Issue Date: **08/02/2023**

Premier Sports Coatings US Blue - 2534

Print Date: 08/02/2023

ethylene glycol is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

 ${\it US-California\ Proposition\ 65-Maximum\ Allowable\ Dose\ Levels\ (MADLs)\ for\ Chemicals\ Causing\ Reproductive\ Toxicity }$

US - California Proposition 65 - Reproductive Toxicity

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)

carbon black is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

US EPA Integrated Risk Information System (IRIS)

US NIOSH Recommended Exposure Limits (RELs)

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US Clean Air Act - Hazardous Air Pollutants

US EPCRA Section 313 Chemical List

US OSHA Permissible Exposure Limits (PELs) Table Z-1 US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Titanium Dioxide Ti02 is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

silica crystalline - quartz is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

US National Toxicology Program (NTP) 15th Report Part A Known to be Human Carcinogens

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Carcinogens Listing

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate is found on the following regulatory lists

US DOE Temporary Emergency Exposure Limits (TEELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	

Version No: 3.3 Page 10 of 11 Issue Date: 08/02/2023 Print Date: 08/02/2023

Premier Sports Coatings US Blue - 2534

No Respiratory or Skin Sensitization Serious eye damage or eye irritation No Specific target organ toxicity (single or repeated exposure) Yes Aspiration Hazard No Germ cell mutagenicity No Simple Asphyxiant No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
ethylene glycol	5000	2270

State Regulations

US. California Proposition 65

Hazards Not Otherwise Classified



MARNING: This product can expose you to chemicals including carbon black, Titanium Dioxide Ti02, silica crystalline - quartz, which are known to the State of California to cause cancer, and ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (ethylene glycol; carbon black; Titanium Dioxide Ti02; silica crystalline - quartz; 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	08/02/2023
Initial Date	07/31/2023

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

SDS Version Summary

Version	Date of Update	Sections Updated
2.3	08/02/2023	Hazards identification - Classification, Composition / information on ingredients - Ingredients

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit.

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value

LOD: Limit Of Detection

No

Version No: 3.3 Page 11 of 11 Issue Date: 08/02/2023

Premier Sports Coatings US Blue - 2534

Print Date: 08/02/2023

OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.