

# **ICP Construction Inc.**

Version No: 3.3

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: 08/16/2023 Print Date: 08/16/2023 S.GHS.USA.EN

# **SECTION 1 Identification**

# Product Identifier

Product name	Plexichrome Ultra Performance Black - PLBL
Synonyms	Not Available
Other means of identification	Not Available

### Recommended use of the chemical and restrictions on use

Relevant identified uses Sports Surface

### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction Inc.
Address	150 Dascomb Road Andover, MA 01810 United States
Telephone	1-866-667-5119 1-978-623-9987
Fax	Not Available
Website	www.icpgroup.com
Email	sds@icpgroup.com

#### Emergency phone number

Association / Organisation	ChemTel	
Emergency telephone numbers	1-800-255-3924	
Other emergency telephone numbers	1-813-248-0585	

# SECTION 2 Hazard(s) identification

# Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification Carcinogenicity Category 1A, Specific Target Organ Toxicity - Repeated Exposure Category 2

#### Label elements

Hazard pictogram(s)	
Signal word	Danger

Hazard statement(s)

H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

# Hazard(s) not otherwise classified

Not Applicable

### Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.

# Precautionary statement(s) Prevention

, ,,	
P201	Obtain special instructions before use.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves and protective clothing.
P202	Do not handle until all safety precautions have been read and understood.

# Precautionary statement(s) Response

• • • • •	•
P308+P313	IF exposed or concerned: Get medical advice/ attention.
P314	Get medical advice/attention if you feel unwell.

Precautionary statement(s) Sto	orage
P405	Store locked up.

# Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

#### **SECTION 3 Composition / information on ingredients**

### Substances

See section below for composition of Mixtures

# Mixtures

CAS No	%[weight]	Name
107-21-1	0.5-1.5	ethylene glycol
14808-60-7*	10-30	silica crystalline - quartz
14464-46-1	1-5	cristobalite

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

## **SECTION 4 First-aid measures**

#### Description of first aid measures

Eye Contact	<ul> <li>If this product comes in contact with eyes:</li> <li>Wash out immediately with water.</li> <li>If irritation continues, seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>	
Skin Contact	If skin contact occurs: <ul> <li>Immediately remove all contaminated clothing, including footwear.</li> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>	
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>	
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>	

# Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5 Fire-fighting measures**

# Extinguishing media

- Foam.
- Dry chemical powder.

# Special hazards arising from the substrate or mixture

Fire Incompatibility		Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	--	--

# Special protective equipment and precautions for fire-fighters

Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear full body protective clothing with breathing apparatus.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Combustible.</li> <li>Slight fire hazard when exposed to heat or flame.</li> <li>Combustion products include:</li> <li>carbon dioxide (CO2)</li> <li>other pyrolysis products typical of burning organic material.</li> <li>May emit poisonous fumes.</li> <li>May emit corrosive fumes.</li> </ul>

# **SECTION 6 Accidental release measures**

# Personal precautions, protective equipment and emergency procedures See section 8

Environmental precautions

See section 12

# Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> </ul>
Major Spills	Moderate hazard.  Clear area of personnel and move upwind.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

# Safe handling Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. DO NOT allow clothing wet with material to stay in contact with skin Store in original containers. Keep containers securely sealed. Item to the secure of the secu

# Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Metal can or drum</li> <li>Packaging as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	Avoid reaction with oxidising agents

# **SECTION 8 Exposure controls / personal protection**

# **Control parameters**

# Occupational Exposure Limits (OEL)

INGREDIENT I	DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	ethylene glycol	Ethylene glycol	Not Available	Not Available	Not Available	See Appendix D
US OSHA Permissible Exposure Limits (PELs) Table Z-1	silica crystalline - quartz	Quartz - respirable	0.05 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	silica crystalline - quartz	Silica: Crystalline: Quartz (Respirable)	10 (%SiO2+2) mg/m3 / 250 (%SiO2+5) mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	silica crystalline - quartz	Silica, crystalline (as respirable dust)	0.05 mg/m3	Not Available	Not Available	Ca; See Appendix A
US OSHA Permissible Exposure Limits (PELs) Table Z-1	cristobalite	Cristobalite - respirable	0.05 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	cristobalite	Silica: Crystalline: Cristobalite	Not Available	Not Available	Not Available	Use ½ the value calculated from the count or mass formulae for quartz.

Source	Ingredient	Material name	TWA	A	STEL	Peak		Notes
US NIOSH Recommended Exposure Limits (RELs)	cristobalite	Particulates not otherwise regulated	Not	Available	Not Available	Not Availa	able	See Appendix D
Emergency Limits								
Ingredient	TEEL-1			TEEL-2			TEEL-	3
ethylene glycol	30 ppm			150 ppm			900 pp	m
silica crystalline - quartz	0.075 mg/m3			33 mg/m3			200 mg	g/m3
cristobalite	0.075 mg/m3			33 mg/m3			200 mg	g/m3
Ingredient	Original IDLH				Rev	ised IDI	.н	
ethylene glycol	Not Available				Not	Availabl	e	
silica crystalline - quartz	25 mg/m3 / 50 m	g/m3			Not	Availabl	е	
cristobalite	Not Available				Not	Availabl	е	

#### Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
Individual protection measures, such as personal protective equipment	
Eye and face protection	<ul> <li>Safety glasses with side shields.</li> <li>Chemical goggles.</li> </ul>
Skin protection	See Hand protection below
Hands/feet protection	<ul> <li>Wear chemical protective gloves, e.g. PVC.</li> <li>Wear safety footwear or safety gumboots, e.g. Rubber</li> <li>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</li> </ul>
Body protection	See Other protection below
Other protection	<ul> <li>Overalls.</li> <li>P.V.C apron.</li> </ul>

#### **Respiratory protection**

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

If inhalation risk above the TLV exists, wear approved dust respirator.

- Use respirators with protection factors appropriate for the exposure level.
- Up to 5 X TLV, use valveless mask type; up to 10 X TLV, use 1/2 mask dust respirator
- ▶ Up to 50 X TLV, use full face dust respirator or demand type C air supplied respirator
- ▶ Up to 500 X TLV, use powered air-purifying dust respirator or a Type C pressure demand supplied-air respirator
- Over 500 X TLV wear full-face self-contained breathing apparatus with positive pressure mode or a combination respirator with a Type C positive pressure supplied-air full-face respirator and an auxiliary self-contained breathing apparatus operated in pressure demand or other positive pressure mode
- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

# **SECTION 9 Physical and chemical properties**

#### Information on basic physical and chemical properties

• •			
Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available

Flash point (°C)	>130	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	95

# SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 Toxicological information**

# Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.		
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.		
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.		
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).		
Chronic	Repeated or long-term occupational exposure is likely to pro Strong evidence exists that this substance may cause irreve	eriod (e.g. in an occupational setting) may increase the risk of cancer. oduce cumulative health effects involving organs or biochemical systems. ersible mutations (though not lethal) even following a single exposure. ite blood cells after they injure the lung epithelium. Chronic exposure to crystalline ctions.	
Plexichrome Ultra	тохісіту	IRRITATION	
D. (			
Performance Black - PLBL	Not Available	Not Available	
Performance Black - PLBL	Not Available TOXICITY	Not Available IRRITATION	
Performance Black - PLBL			
Performance Black - PLBL	ΤΟΧΙΟΙΤΥ	IRRITATION	
	TOXICITY dermal (mouse) LD50: >3500 mg/kg <sup>[1]</sup>	IRRITATION Eye (rabbit): 100 mg/1h - mild	
Performance Black - PLBL	TOXICITY dermal (mouse) LD50: >3500 mg/kg <sup>[1]</sup>	IRRITATION Eye (rabbit): 100 mg/1h - mild Eye (rabbit): 12 mg/m3/3D	
	TOXICITY dermal (mouse) LD50: >3500 mg/kg <sup>[1]</sup>	IRRITATION         Eye (rabbit): 100 mg/1h - mild         Eye (rabbit): 12 mg/m3/3D         Eye (rabbit): 1440mg/6h-moderate	
	TOXICITY dermal (mouse) LD50: >3500 mg/kg <sup>[1]</sup>	IRRITATION         Eye (rabbit): 100 mg/1h - mild         Eye (rabbit): 12 mg/m3/3D         Eye (rabbit): 1440mg/6h-moderate         Eye (rabbit): 500 mg/24h - mild	
	TOXICITY dermal (mouse) LD50: >3500 mg/kg <sup>[1]</sup>	IRRITATION         Eye (rabbit): 100 mg/1h - mild         Eye (rabbit): 12 mg/m3/3D         Eye (rabbit): 1440mg/6h-moderate         Eye (rabbit): 500 mg/24h - mild         Eye: no adverse effect observed (not irritating) <sup>[1]</sup>	
	TOXICITY dermal (mouse) LD50: >3500 mg/kg <sup>[1]</sup>	IRRITATION         Eye (rabbit): 100 mg/1h - mild         Eye (rabbit): 12 mg/m3/3D         Eye (rabbit): 1440mg/6h-moderate         Eye (rabbit): 500 mg/24h - mild         Eye: no adverse effect observed (not irritating) <sup>[1]</sup> Skin (rabbit): 555 mg(open)-mild	

	Inhalation (Human)TCLo: 16 mppcf*/8H/17.9Y <sup>[2]</sup>	
	Inhalation (Rat)TCLo: 50 mg/m3/6H/71W <sup>[2]</sup>	
- sinte ballita	TOXICITY	IRRITATION
cristobalite	Not Available	Not Available
Legend:	<ol> <li>Value obtained from Europe ECHA Registered Substances - Acute tox specified data extracted from RTECS - Register of Toxic Effect of chemic</li> </ol>	

Plexichrome Ultra Performance Black - PLBL	Laboratory (in vitro) and animal studies show, exposure to the material may result in a possible risk of irreversible effects, with the possibility of producing mutation.			
ETHYLENE GLYCOL	[Estimated Lethal Dose (human) 100 ml; RTECS quoted by Orica] Substance is reproductive effector in rats (birth defects). Mutagenic to rat cells. For ethylene glycol: Ethylene glycol is quickly and extensively absorbed throughout the gastrointestinal tract. Limited information suggests that it is also absorbed through the airways; absorption through skin is apparently slow.			
CRISTOBALITE	Inhalation (human) TCLo: 16 mppcf*/8H/17.9y-I * Mil	lions of particles per cubic foot		
silica crystalline - quartz & CRISTOBALITE	WARNING: For inhalation exposure <u>ONLY</u> : This substance has been classified by the IARC as Group 1: <b>CARCINOGENIC TO HUMANS</b> The International Agency for Research on Cancer (IARC) has classified occupational exposures to <b>respirable</b> (<5 um) crystalline silica as being carcinogenic to humans. This classification is based on what IARC considered sufficient evidence from epidemiological studies of humans for the carcinogenicity of inhaled silica in the forms of quartz and cristobalite.			
Acute Toxicity	X Carcinogenicity			
Skin Irritation/Corrosion	×	Reproductivity	×	
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×	
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	*	
Mutagenicity	×	Aspiration Hazard	×	
			r not available or does not fill the criteria for classification able to make classification	

# **SECTION 12 Ecological information**

# Toxicity

Endpoint	Test Duration (hr)	Species		Value	Source
Not Available	Not Available	Not Available		Not Available	Not Available
Endpoint	Test Duration (hr)	Species	Val	ue	Source
EC50	96h	Algae or other aquatic plants	650	0-13000mg/l	1
EC50	48h	Crustacea	>10	0mg/l	2
LC50	96h	Fish	805	i0mg/l	4
EC50(ECx)	Not Available	Algae or other aquatic plants	650	00-7500mg/l	1
Endpoint	Test Duration (hr)	Species		Value	Source
Not Available	Not Available	Not Available		Not Available	Not Available
Endpoint	Test Duration (hr)	Species		Value	Source
Not Available	Not Available	Not Available		Not Available	Not Available
	Not AvailableEndpointEC50EC50LC50EC50(ECx)EndpointNot AvailableEndpointNotNot	Not Available     Not Available       Endpoint     Test Duration (hr)       EC50     96h       EC50     48h       LC50     96h       EC50(ECx)     Not Available       Endpoint     Test Duration (hr)       Not Available     Not Available       Endpoint     Test Duration (hr)       Not Available     Not Available       Endpoint     Test Duration (hr)       Not     Not Available       Not     Not Available	Not Available       Not Available       Not Available         Endpoint       Test Duration (hr)       Species         EC50       96h       Algae or other aquatic plants         EC50       48h       Crustacea         LC50       96h       Fish         EC50(ECx)       Not Available       Algae or other aquatic plants         Endpoint       Test Duration (hr)       Species         Not Available       Not Available       Not Available         Not Available       Not Available       Not Available         Endpoint       Test Duration (hr)       Species         Not Available       Not Available       Not Available         Not       Not Available       Not Available         Not       Not Available       Not Available	Not Available       Not Available       Not Available         Endpoint       Test Duration (hr)       Species       Val         EC50       96h       Algae or other aquatic plants       650         EC50       48h       Crustacea       >10         LC50       96h       Fish       805         EC50(ECx)       Not Available       Algae or other aquatic plants       650         Endpoint       Test Duration (hr)       Species       Val         Not Available       Not Available       Not Available       Not Available         Not Available       Not Available       Not Available       Not Available         Not Available       Not Available       Not Available       Not Available	Not Available         Not Available         Not Available         Not Available           Endpoint         Test Duration (hr)         Species         Value           EC50         96h         Algae or other aquatic plants         6500-13000mg/l           EC50         48h         Crustacea         >100mg/l           LC50         96h         Fish         8050mg/l           EC50(ECx)         Not Available         Algae or other aquatic plants         6500-7500mg/l           Endpoint         Test Duration (hr)         Species         Value           Not Available         Not Available         Not Available         Not Available           Not Available         Not Available         Not Available         Not Available           Not Available         Not Available         Not Available         Not Available

- Bioconcentration Data 8. Vendor Data

# DO NOT discharge into sewer or waterways.

# Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethylene glycol	LOW (Half-life = 24 days)	LOW (Half-life = 3.46 days)

Bioaccumulative poter	ıtial	
Ingredient	Bioaccumulation	
ethylene glycol	LOW (BCF = 200)	
lobility in soil		

Ingredient	Mobility
ethylene glycol	HIGH (KOC = 1)

# **SECTION 13 Disposal considerations**

Waste treatment methods	
Product / Packaging disposal	<ul> <li>Containers may still present a chemical hazard/ danger when empty.</li> <li>Return to supplier for reuse/ recycling if possible.</li> <li>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.</li> <li>DO NOT allow wash water from cleaning or process equipment to enter drains.</li> <li>It may be necessary to collect all wash water for treatment before disposal.</li> <li>Recycle wherever possible or consult manufacturer for recycling options.</li> <li>Consult State Land Waste Authority for disposal.</li> </ul>

# **SECTION 14 Transport information**

# Labels Required

Marine Pollutant NO

Shipping container and transport vehicle placarding and labeling may vary from the below information. Products that are regulated for transport will be packaged and marked as Dangerous Goods in Limited Quantities according to US DOT, IATA and IMDG regulations. In case of reshipment, it is the responsibility of the shipper to determine the appropriate labels and markings in accordance with applicable transport regulations.

# Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

#### Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

#### Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

#### Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
ethylene glycol	Not Available
silica crystalline - quartz	Not Available
cristobalite	Not Available

#### Transport in bulk in accordance with the IGC Code

Product name	Ship Type
ethylene glycol	Not Available
silica crystalline - quartz	Not Available
cristobalite	Not Available

#### **SECTION 15 Regulatory information**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

# ethylene glycol is found on the following regulatory lists

- Chemical Footprint Project Chemicals of High Concern List
- US California Hazardous Air Pollutants Identified as Toxic Air Contaminants
- US California Proposition 65 Maximum Allowable Dose Levels (MADLs) for
- Chemicals Causing Reproductive Toxicity
- US California Proposition 65 Reproductive Toxicity
- US California Safe Drinking Water and Toxic Enforcement Act of 1986 Proposition 65 List
- US Massachusetts Right To Know Listed Chemicals
- US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)

# silica crystalline - quartz is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

cristobalite is found on the following regulatory lists

- US Clean Air Act Hazardous Air Pollutants
- US DOE Temporary Emergency Exposure Limits (TEELs)
- US EPA Integrated Risk Information System (IRIS)

US EPCRA Section 313 Chemical List

US NIOSH Recommended Exposure Limits (RELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US National Toxicology Program (NTP) 15th Report Part A Known to be Human Carcinogens

US NIOSH Carcinogen List

- US NIOSH Recommended Exposure Limits (RELs)
- US OSHA Carcinogens Listing
- US OSHA Permissible Exposure Limits (PELs) Table Z-1
- US OSHA Permissible Exposure Limits (PELs) Table Z-3
- US Toxic Substances Control Act (TSCA) Chemical Substance Inventory

Chemical Footprint Project - Chemicals of High Concern List US NIOSH Carcinogen List International WHO List of Proposed Occupational Exposure Limit (OEL) Values for US NIOSH Recommended Exposure Limits (RELs) Manufactured Nanomaterials (MNMS) US OSHA Carcinogens Listing US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for US OSHA Permissible Exposure Limits (PELs) Table Z-1 Air Pollutants Other Than PM-2.5 US OSHA Permissible Exposure Limits (PELs) Table Z-3 US - California Proposition 65 - Carcinogens US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List US - Massachusetts - Right To Know Listed Chemicals US DOE Temporary Emergency Exposure Limits (TEELs)

**Federal Regulations** 

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

# Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	Yes
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

Name	Reportable Quantity in Pounds (Ib)	Reportable Quantity in kg
ethylene glycol	5000	2270

#### State Regulations

# US. California Proposition 65

MARNING: This product can expose you to chemicals including silica crystalline - quartz, cristobalite, which are known to the State of California to cause cancer, and ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

#### National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (ethylene glycol; silica crystalline - quartz; cristobalite)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes

National Inventory	Status
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration

#### **SECTION 16 Other information**

Revision Date	08/16/2023	
Initial Date	08/02/2023	

# CONTACT POINT

\*\*PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES\*\*

#### SDS Version Summary

Version	Date of Update	Sections Updated
2.3	08/16/2023	Hazards identification - Classification, Composition / information on ingredients - Ingredients

### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

#### **Definitions and abbreviations**

PC - TWA: Permissible Concentration-Time Weighted Average PC - STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.