



Ti-Coat Epoxy B 'Waterbase' 3904

ICP Construction Inc.

Version No: 8.8

Safety Data Sheet according to OSHA HazCom Standard (2024) requirements

Initial Date: 03/05/2017

Revision Date: 05/07/2026

Print Date: 05/07/2026

S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	Ti-Coat Epoxy B 'Waterbase' 3904
Synonyms	Not Available
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	Adhesion promoter for concrete surfaces
--------------------------	---

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction Inc.
Address	150 Dascomb Road Andover, MA 01810 United States
Telephone	1-866-667-5119 1-978-623-9987
Fax	Not Available
Website	www.icpgroup.com
Email	sds@icpgroup.com

Emergency phone number

Association / Organisation	ChemTel
Emergency telephone number(s)	1-800-255-3924
Other emergency telephone number(s)	1-813-248-0585

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health, Red = Fire, Yellow = Reactivity and White = Special (Oxidizer or water reactive substances)

Classification	Skin Corrosion/Irritation Category 1B, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 1
----------------	--

Label elements

Hazard pictogram(s)	
---------------------	--

Signal word	Danger
-------------	---------------

Hazard statement(s)

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.

Hazard(s) not otherwise classified

Not Applicable

Ti-Coat Epoxy B "Waterbase" 3904

Precautionary statement(s) Prevention

P260	Do not breathe mist/vapours/spray.
P264	Wash all exposed external body areas thoroughly after handling.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P261	Avoid breathing mist/vapours/spray.
P272	Contaminated work clothing must not be allowed out of the workplace.

Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P363	Wash contaminated clothing before reuse.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary statement(s) Storage

P405	Store locked up.
------	------------------

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
10563-29-8	10-30	<u>dimethyldipropylenetriamine</u>
2807-30-9	5-10	<u>2-propoxyethanol</u>
124-17-4	1-5	<u>diethylene glycol monobutyl ether acetate</u>

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: ▶ Immediately hold eyelids apart and flush the eye continuously with running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: ▶ Immediately flush body and clothes with large amounts of water, using safety shower if available. ▶ Quickly remove all contaminated clothing, including footwear. ▶ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. ▶ Transport to hospital, or doctor.
Inhalation	▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor.
Ingestion	▶ For advice, contact a Poisons Information Centre or a doctor at once. ▶ Urgent hospital treatment is likely to be needed. ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Transport to hospital or doctor without delay.

Most important symptoms and effects, both acute and delayed

See Section 11

Continued...

Indication of any immediate medical attention and special treatment needed

For acute or short-term repeated exposures to highly alkaline materials:

- ▶ Respiratory stress is uncommon but present occasionally because of soft tissue edema.
- ▶ Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.
- ▶ Oxygen is given as indicated.
- ▶ The presence of shock suggests perforation and mandates an intravenous line and fluid administration.
- ▶ Damage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue.

Alkalis continue to cause damage after exposure.

INGESTION:

- ▶ Milk and water are the preferred diluents

No more than 2 glasses of water should be given to an adult.

- ▶ Neutralising agents should never be given since exothermic heat reaction may compound injury.

* Catharsis and emesis are absolutely contra-indicated.

* Activated charcoal does not absorb alkali.

* Gastric lavage should not be used.

Supportive care involves the following:

- ▶ Withhold oral feedings initially.
- ▶ If endoscopy confirms transmucosal injury start steroids only within the first 48 hours.
- ▶ Carefully evaluate the amount of tissue necrosis before assessing the need for surgical intervention.
- ▶ Patients should be instructed to seek medical attention whenever they develop difficulty in swallowing (dysphagia).

SKIN AND EYE:

- ▶ Injury should be irrigated for 20-30 minutes.

Eye injuries require saline. [Ellenhorn & Barceloux: Medical Toxicology]

SECTION 5 Fire-fighting measures

Extinguishing media

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	--

Special protective equipment and precautions for fire-fighters

Fire Fighting	▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear full body protective clothing with breathing apparatus. ▶ Prevent, by any means available, spillage from entering drains or water course.
Fire/Explosion Hazard	▶ Combustible. ▶ Slight fire hazard when exposed to heat or flame. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. Combustion products include: ▶ carbon dioxide (CO2) ▶ nitrogen oxides (NOx) ▶ other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	▶ Remove all ignition sources. ▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes.
Major Spills	Moderate hazard. ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	▶ Avoid skin contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ DO NOT allow clothing wet with material to stay in contact with skin
Other information	▶ Store in original containers. ▶ Keep containers securely sealed. ▶ No smoking, naked lights or ignition sources.

Conditions for safe storage, including any incompatibilities

Suitable container	▶ Metal can or drum ▶ Packaging as recommended by manufacturer. ▶ Check all containers are clearly labelled and free from leaks.
--------------------	--

Ti-Coat Epoxy B "Waterbase" 3904

Storage incompatibility

- ▶ Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.
- ▶ Avoid contact with copper, aluminium and their alloys.
- ▶ Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
2-propoxyethanol	2.2 ppm	24 ppm	140 ppm

Ingredient	Original IDLH	Revised IDLH
dimethyldipropylenetriamine	Not Available	Not Available
2-propoxyethanol	Not Available	Not Available
diethylene glycol monobutyl ether acetate	Not Available	Not Available

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk.
Individual protection measures, such as personal protective equipment	
Eye and face protection	▶ Chemical goggles. ▶ Full face shield may be required for supplementary but never for primary protection of eyes. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.
Skin protection	See Hand protection below
Hands/feet protection	▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber ▶ When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. NOTE: ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.
Body protection	See Other protection below
Other protection	▶ Overalls. ▶ P.V.C apron. ▶ Barrier cream.

Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Text		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available

Continued...

Ti-Coat Epoxy B "Waterbase" 3904

Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	>130	Taste	Not Available
Evaporation rate	Not Available BuAC = 1	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	191 when mixed as intended
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	There is sufficient evidence to classify this material as skin corrosive or irritating.
c) Serious Eye Damage/Irritation	There is sufficient evidence to classify this material as eye damaging or irritating
d) Respiratory or Skin sensitisation	There is sufficient evidence to classify this material as sensitising to skin or the respiratory system
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.
j) Aspiration Hazard	Based on available data, the classification criteria are not met.

Inhaled	The material is not thought to produce adverse health effects following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Inhalation of amine vapours may cause irritation of the mucous membrane of the nose and throat, and lung irritation with respiratory distress and cough. Swelling and inflammation of the respiratory tract is seen in serious cases; with headache, nausea, faintness and anxiety. Inhalation of epoxy resin amine hardeners (including polyamines and amine adducts) may produce bronchospasm and coughing episodes lasting several days after cessation of the exposure. Even faint traces of these vapours may trigger an intense reaction in individuals showing 'amine asthma'. Inhalation hazard is increased at higher temperatures.
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion. Amines without benzene rings when swallowed are absorbed throughout the gut. Corrosive action may cause damage throughout the gastrointestinal tract. Ingestion of amine epoxy-curing agents (hardeners) may cause severe abdominal pain, nausea, vomiting or diarrhoea. The vomitus may contain blood and mucous.
Skin Contact	The material can produce chemical burns following direct contact with the skin. Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. Amine epoxy-curing agents (hardeners) may produce primary skin irritation and sensitisation dermatitis in predisposed individuals. Cutaneous reactions include erythema, intolerable itching and severe facial swelling. Volatile amine vapours produce irritation and inflammation of the skin. Direct contact can cause burns. Open cuts, abraded or irritated skin should not be exposed to this material. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. If applied to the eyes, this material causes severe eye damage.

Continued...

Ti-Coat Epoxy B "Waterbase" 3904

	Vapours of volatile amines irritate the eyes, causing excessive secretion of tears, inflammation of the conjunctiva and slight swelling of the cornea, resulting in 'halos' around lights. This effect is temporary, lasting only for a few hours. However this condition can reduce the efficiency of undertaking skilled tasks, such as driving a car.														
Chronic	Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems. Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Amine epoxy-curing agents (hardeners) may produce primary skin irritation and sensitisation dermatitis in predisposed individuals. Cutaneous reactions include erythema, intolerable itching and severe facial swelling.														
Ti-Coat Epoxy B 'Waterbase' 3904	<table> <tr> <th>TOXICITY</th><th>IRRITATION</th></tr> <tr> <td>Not Available</td><td>Not Available</td></tr> </table>	TOXICITY	IRRITATION	Not Available	Not Available										
TOXICITY	IRRITATION														
Not Available	Not Available														
dimethyldipropylenetriamine	<table> <tr> <th>TOXICITY</th><th>IRRITATION</th></tr> <tr> <td>Dermal (rabbit) LD50: 1300 mg/kg^[2]</td><td>Eye: adverse effect observed (irritating)^[1]</td></tr> <tr> <td>Oral (Rat) LD50: 1545 mg/kg^[1]</td><td>Skin: adverse effect observed (corrosive)^[1]</td></tr> </table>	TOXICITY	IRRITATION	Dermal (rabbit) LD50: 1300 mg/kg ^[2]	Eye: adverse effect observed (irritating) ^[1]	Oral (Rat) LD50: 1545 mg/kg ^[1]	Skin: adverse effect observed (corrosive) ^[1]								
TOXICITY	IRRITATION														
Dermal (rabbit) LD50: 1300 mg/kg ^[2]	Eye: adverse effect observed (irritating) ^[1]														
Oral (Rat) LD50: 1545 mg/kg ^[1]	Skin: adverse effect observed (corrosive) ^[1]														
2-propoxyethanol	<table> <tr> <th>TOXICITY</th><th>IRRITATION</th></tr> <tr> <td>Dermal (rabbit) LD50: 960 mg/kg^[2]</td><td>Eye (Rodent - rabbit): 100mg - Severe</td></tr> <tr> <td>Inhalation (Rat) LC50: >2300 ppm4h^[1]</td><td>Eye (Rodent - rabbit): 750ug/24H - Severe</td></tr> <tr> <td>Oral (Rat) LD50: 3089 mg/kg^[2]</td><td>Eye: adverse effect observed (irritating)^[1]</td></tr> <tr> <td></td><td>Skin (Rodent - guinea pig): 1mL/24H - Mild</td></tr> <tr> <td></td><td>Skin (Rodent - rabbit): 500mg/24H - Mild</td></tr> <tr> <td></td><td>Skin: adverse effect observed (irritating)^[1]</td></tr> </table>	TOXICITY	IRRITATION	Dermal (rabbit) LD50: 960 mg/kg ^[2]	Eye (Rodent - rabbit): 100mg - Severe	Inhalation (Rat) LC50: >2300 ppm4h ^[1]	Eye (Rodent - rabbit): 750ug/24H - Severe	Oral (Rat) LD50: 3089 mg/kg ^[2]	Eye: adverse effect observed (irritating) ^[1]		Skin (Rodent - guinea pig): 1mL/24H - Mild		Skin (Rodent - rabbit): 500mg/24H - Mild		Skin: adverse effect observed (irritating) ^[1]
TOXICITY	IRRITATION														
Dermal (rabbit) LD50: 960 mg/kg ^[2]	Eye (Rodent - rabbit): 100mg - Severe														
Inhalation (Rat) LC50: >2300 ppm4h ^[1]	Eye (Rodent - rabbit): 750ug/24H - Severe														
Oral (Rat) LD50: 3089 mg/kg ^[2]	Eye: adverse effect observed (irritating) ^[1]														
	Skin (Rodent - guinea pig): 1mL/24H - Mild														
	Skin (Rodent - rabbit): 500mg/24H - Mild														
	Skin: adverse effect observed (irritating) ^[1]														
diethylene glycol monobutyl ether acetate	<table> <tr> <th>TOXICITY</th><th>IRRITATION</th></tr> <tr> <td>Dermal (rabbit) LD50: 14500 mg/kg^[2]</td><td>Eye (Rodent - rabbit): 500mg - Moderate</td></tr> <tr> <td>Inhalation (Rat) LC50: 72.5 mg/L4h^[2]</td><td>Eye: no adverse effect observed (not irritating)^[1]</td></tr> <tr> <td>Oral (Rabbit) LD50: 2260 mg/kg^[2]</td><td>Skin (Rodent - rabbit): 500mg - Mild</td></tr> <tr> <td></td><td>Skin: no adverse effect observed (not irritating)^[1]</td></tr> </table>	TOXICITY	IRRITATION	Dermal (rabbit) LD50: 14500 mg/kg ^[2]	Eye (Rodent - rabbit): 500mg - Moderate	Inhalation (Rat) LC50: 72.5 mg/L4h ^[2]	Eye: no adverse effect observed (not irritating) ^[1]	Oral (Rabbit) LD50: 2260 mg/kg ^[2]	Skin (Rodent - rabbit): 500mg - Mild		Skin: no adverse effect observed (not irritating) ^[1]				
TOXICITY	IRRITATION														
Dermal (rabbit) LD50: 14500 mg/kg ^[2]	Eye (Rodent - rabbit): 500mg - Moderate														
Inhalation (Rat) LC50: 72.5 mg/L4h ^[2]	Eye: no adverse effect observed (not irritating) ^[1]														
Oral (Rabbit) LD50: 2260 mg/kg ^[2]	Skin (Rodent - rabbit): 500mg - Mild														
	Skin: no adverse effect observed (not irritating) ^[1]														
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of Chemical Substances														

DIMETHYLDIPROPYLENETRIAMINE	Skin allergy was observed in guinea pigs following repeated exposure. tests using bacteria ** Hoechst MSDS ** Arkema MSDS The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function. Overexposure to most of these materials may cause adverse health effects. Many amine-based compounds can cause release of histamines, which, in turn, can trigger allergic and other physiological effects, including constriction of the bronchi or asthma and inflammation of the cavity of the nose. Whole-body symptoms include headache, nausea, faintness, anxiety, a decrease in blood pressure, rapid heartbeat, itching, reddening of the skin, urticaria (hives) and swelling of the face, which are usually transient. There are generally four routes of possible or potential exposure: inhalation, skin contact, eye contact, and swallowing. Inhalation: Inhaling vapours may result in moderate to severe irritation of the tissues of the nose and throat and can irritate the lungs. Higher concentrations of certain amines can produce severe respiratory irritation, characterized by discharge from the nose, coughing, difficulty in breathing and chest pain.
2-PROPOXYETHANOL	There have been no specific human studies, but the consistency of the animal experiments emphasizes that human exposure should be dramatically reduced. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. For ethylene glycol monoalkyl ethers and their acetates (EGMAEs): Typical members of this category are ethylene glycol propylene ether (EGPE), ethylene glycol butyl ether (EGBE) and ethylene glycol hexyl ether (EGHE) and their acetates. EGMAEs are substrates for alcohol dehydrogenase isozyme ADH-3, which catalyzes the conversion of their terminal alcohols to aldehydes (which are transient metabolites). Further, rapid conversion of the aldehydes by aldehyde dehydrogenase produces alkoxyacetic acids, which are the predominant urinary metabolites of mono substituted glycol ethers. Acute Toxicity: Oral LD50 values in rats for all category members range from 739 (EGHE) to 3089 mg/kg bw (EGPE), with values increasing with decreasing molecular weight. Four to six hour acute inhalation toxicity studies were conducted for these chemicals in rats at the highest vapour concentrations practically achievable.
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE	The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. This category includes diethylene glycol ethyl ether (DGEE), diethylene glycol propyl ether (DGPE) diethylene glycol butyl ether (DGBE) and diethylene glycol hexyl ether (DGHE) and their acetates. Studies show that they can cause kidney and liver damage, skin and eye irritation as well as blood changes but do not cause damage to the reproductive, genetic and developmental abnormalities, sensitisation or respiratory systems. However, DGEE is reported to cause sperm insufficiency.
Ti-Coat Epoxy B 'Waterbase' 3904 & DIMETHYLDIPROPYLENETRIAMINE	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant.

Ti-Coat Epoxy B "Waterbase" 3904

DIMETHYLDIPROPYLENETRIAMINE & 2-PROPOXYETHANOL & DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE		The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.	
Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✓	Reproductivity	✗
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity					
Ti-Coat Epoxy B 'Waterbase' 3904	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
dimethyldipropylenetriamine	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	7.3mg/l	2
	EC50	48h	Crustacea	9.22mg/l	2
	EC10(ECx)	72h	Algae or other aquatic plants	1.9mg/l	2
	LC50	96h	Fish	>100mg/l	2
2-propoxyethanol	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>100mg/l	2
	NOEC(ECx)	72h	Algae or other aquatic plants	>=100mg/l	2
	LC50	96h	Fish	>91.3mg/l	Not Available
diethylene glycol monobutyl ether acetate	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>500mg/l	2
	EC10(ECx)	168h	Crustacea	10.84mg/l	2
	EC50	96h	Algae or other aquatic plants	75mg/l	2
	LC50	96h	Fish	50mg/l	1
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data				

For Ethelene Glycol Monoalkyl Ethers and their Acetates:
log BCF: 0.463 to 0.732;
LC50 : 94 to > 5000 mg/L. (aquatic species).
Members of this category include ethylene glycol propyl ether (EGPE), ethylene glycol butyl ether (EGBE) and ethylene glycol hexyl ether (EGHE).
DO NOT discharge into sewer or waterways.

Persistence and degradability		
Ingredient	Persistence: Water/Soil	Persistence: Air
dimethyldipropylenetriamine	HIGH	HIGH
2-propoxyethanol	LOW	LOW
diethylene glycol monobutyl ether acetate	LOW	LOW

Bioaccumulative potential	
Ingredient	Bioaccumulation
dimethyldipropylenetriamine	LOW (LogKOW = -0.47)
2-propoxyethanol	LOW (LogKOW = 0.0755)
diethylene glycol monobutyl ether acetate	LOW (LogKOW = 1.3)

Mobility in soil	
Ingredient	Mobility
dimethyldipropylenetriamine	LOW (Log KOC = 479.2)
2-propoxyethanol	HIGH (Log KOC = 1)
diethylene glycol monobutyl ether acetate	LOW (Log KOC = 10)

Ti-Coat Epoxy B "Waterbase" 3904

Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	- Containers may still present a chemical hazard/ danger when empty. - Return to supplier for reuse/ recycling if possible.
	Otherwise: - If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. DO NOT allow wash water from cleaning or process equipment to enter drains. - It may be necessary to collect all wash water for treatment before disposal. - In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. - Recycle wherever possible or consult manufacturer for recycling options. - Consult State Land Waste Authority for disposal. - Bury or incinerate residue at an approved site.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
------------------	----

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
dimethyldipropylenetriamine	Not Applicable
2-propoxyethanol	Not Applicable
diethylene glycol monobutyl ether acetate	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
dimethyldipropylenetriamine	Not Applicable
2-propoxyethanol	Not Applicable
diethylene glycol monobutyl ether acetate	Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

dimethyldipropylenetriamine is found on the following regulatory lists

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

2-propoxyethanol is found on the following regulatory lists

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US - Pennsylvania - Hazardous Substance List

US Clean Air Act - Hazardous Air Pollutants

US DOE Temporary Emergency Exposure Limits (TEELs)

US EPCRA Section 313 Chemical List

US New York City Community Right-to-Know: List of Hazardous Substances

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

diethylene glycol monobutyl ether acetate is found on the following regulatory lists

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US - Pennsylvania - Hazardous Substance List

US New York City Community Right-to-Know: List of Hazardous Substances

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Section 4/12 (b) - Sunset Dates/Status

Additional Regulatory Information

Not Applicable

Continued...

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	Yes
Respiratory or Skin Sensitization	Yes
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

US. EPCRA Section 313 Toxic Release Inventory (TRI) (40 CFR 372)

This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know-Act of 1986 (40 CFR 372):

CAS No	%[weight]	Name
2807-30-9	5-10	2-propoxyethanol

This information must be included in all SDSs that are copied and distributed for this material.

Additional Federal Regulatory Information

Not Applicable

State Regulations

US. California Proposition 65

None Reported

Additional State Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (dimethyldipropylenetriamine; 2-propoxyethanol; diethylene glycol monobutyl ether acetate)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'

Ti-Coat Epoxy B "Waterbase" 3904

National Inventory	Status
Taiwan - TCSI	Yes
Mexico - INSQ	No (dimethyldipropylenetriamine; 2-propoxyethanol)
Vietnam - NCI	Yes
Russia - FBEPH	Yes
UAE - Control List (Banned/Restricted Substances)	No (dimethyldipropylenetriamine; 2-propoxyethanol; diethylene glycol monobutyl ether acetate)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	05/07/2026
Initial Date	03/05/2017

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

SDS Version Summary

Version	Date of Update	Sections Updated
7.8	05/07/2026	Toxicological information - Acute Health (skin), Hazards identification - Classification, Composition / information on ingredients - Ingredients, Name

Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.

Powered by AuthorITe, from Chemwatch.