



**Plexitrac® Line Paint No. 6022 White**  
**LATEX LINE MARKING PAINT FOR URETHANE ATHLETIC SURFACES**

**DESCRIPTION**

A highly reflective marking paint for use over urethane athletic surfaces, intended for the striping of urethane running tracks. Can also be used on asphalt or concrete surface in light traffic areas, such as athletic courts, play areas, running tracks, & parking lots.

**Substrate Cure Requirements**

Existing urethane running surfaces must be cured a minimum of 24 hours prior to striping. New hot-mix asphalt surfaces must be allowed 14 days minimum cure time prior to application of Line Paint. For new concrete surfaces, a minimum of 28 days cure time is required.

**MIXING/APPLICATION INSTRUCTIONS**

California Plexitrac Line Paint comes ready to apply. Only gentle stirring is necessary. DO NOT DILUTE.

- Brush
- Roller
- Spray & Marking Equipment
- Airless Spray

**Drying and Cure Time**

California Plexitrac Line Paint must be allowed to dry for 1 hour between coating applications. Completed projects should be allowed 12 hours before releasing to play.

**COVERAGE**

Approximately 150-200 square feet per gallon.

**LIMITATIONS**

- Do not apply when rain or high humidity is imminent.
- Not for application on general use roadways subjected to skidding tires, snowplows, or chains.
- Keep from freezing. Do not store in hot sun.
- Keep containers tightly closed when not in use.
- Do not apply when surface temperature is less than 55°F/13°C or more than 130°F/55°C.
- Allow new asphalt to cure at least 14 days
- Allow new concrete to cure no less than 28 days